

NEW MEXICO OIL CONSERVATION COMMISSION

MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission District Office within ten days after the work specified is completed. It should be signed and filed as a report on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS	REPORT ON REPAIRING WELL
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL	REPORT ON PULLING OR OTHERWISE ALTERING CASING
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	REPORT ON DEEPENING WELL
REPORT ON RESULT OF PLUGGING OF WELL	Report on Plugging Back XX

March 15, 1952 - Hobbs, New Mexico

Date

Place

Following is a report on the work done and the results obtained under the heading noted above at the.....

Skelly Oil Company Mexico "L" Well No. **2** in the
 Company or Operator Lease
SE/4 NE/4 of Sec. **5** T. **25S** R. **38E**, N. M. P. M.,
Unnamed Pool **Lea** County.

The dates of this work were as follows: **March 9 to March 12, 1952.**

Notice of intention to do the work was ~~received~~ submitted on Form C-102 on **March 8,** 19**52.**
 and approval of the proposed plan was ~~received~~ obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Drilled to a total depth of 10,615'. Drill-stem test 10,565-615'. Recovered 2131' of black sulphur water. No show of oil or gas. Went in hole with open end drill pipe and ran 50 sacks cement 10,484-615', heavy mud-laden fluid 8,931-10,848', 50 sacks cement 8800-8931'. Checked top of cement plug and could not find any cement. Circulated out loose cement that had not set. Ran 50 sacks cement 8800, 8931, preceded with 20 bbls. caustic water, 200# quebracho, 5 bbls. water. Checked top of plug and found plug at 8809'. Cement set up o.k. Ran 5-1/2" OD casing to 8809'.

Witnessed by E. L. Calhoon Skelly Oil Co. Foreman
 Name Company Title

APPROVED:
 OIL CONSERVATION COMMISSION

Rog. Yarbrough
 Name
 Title
 Date

I hereby swear or affirm that the information given above is true and correct.

J. J. Smiley
 Name
 Position **Dist. Supt.**
 Representing **Skelly Oil Co.**
 Company or Operator
 Address **Box 38 - Hobbs, N.M.**