		- 'P	Form C-102
NEW MEXICO OIL		WATION C MISSION	TRAE TO
MISCELL	ANEO	US NOTICES	主語である
Submit this notice in triplicate to the Oil Conservation begin. A copy will be returned to the sender on we divisable, or the rejection by the Commission or ago and work should not begin until approval is obta- the Commission. Indicate nature	which will ent, of the ined. See	be given the approval, with any modifications	considered be followed, ulations of
NOTICE OF INTENTION TO TEST CASING SHUT-OFF		NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL	
NOTICE OF INTENTION TO CHANGE PLANS	XX	NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING	
NOTICE OF INTENTION TO REPAIR WELL		NOTICE OF INTENTION TO PLUG WELL	
NOTICE OF INTENTION TO DEEPEN WELL			
		Hobbs, New Mexico - March 8, 195 Place Date	2.
DIL CONSERVATION COMMISSION, Janta Fe, New Mexico			
Hentlemen:			
Following is a notice of intention to do certain wor	rk as desc	ribed below at the	CE/I NE/I
	8.56		
-	5, N	I. M. P. M.	Field.
Les Count	•		
FLUE DETAILS C			
		POSED PLAN OF WORK	
FOLLOW INSTRUCTIONS IN THE	RULES A	ND REGULATIONS OF THE COMMISSION	5'.
FOLLOW INSTRUCTIONS IN THE Drilled to a total depth of	RULES A	ND REGULATIONS OF THE COMMISSION	5'.
FOLLOW INSTRUCTIONS IN THE Drilled to a total depth of Recovered 2131' of black of	RULES A	AND REGULATIONS OF THE COMMISSION	
FOLLOW INSTRUCTIONS IN THE Drilled to a total depth of Recovered 2131' of black of Propose to plug-back to 85	RULES A of 10,61 sulphur 800'. N	AND REGULATIONS OF THE COMMISSION 15'. Drill stem test 10,565-10,61 water. No show of oil or gas.	
FOLLOW INSTRUCTIONS IN THE Drilled to a total depth of Recovered 2131' of black a Propose to plug-back to 88 10615', then cement from a	RULES A of 10,61 sulphur 800'. N 8800 to	AND REGULATIONS OF THE COMMISSION 15'. Drill stem test 10,565-10,63 water. No show of oil or gas. Will cement with 50 sacks, 10484 t	59
FOLLOW INSTRUCTIONS IN THE Drilled to a total depth of Recovered 2131' of black of Propose to plug-back to 80 10615', then cement from 2	RULES A of 10,61 sulphur 800'. 5 8800 to , set re	AND REGULATIONS OF THE COMMISSION 15'. Drill stem test 10,565-10,61 water. No show of oil or gas. Will cement with 50 sacks, 10484 to 8931' with 50 sacks. Will run stainer and prepare to complete we	59
Follow INSTRUCTIONS IN THE Drilled to a total depth of Recovered 2131' of black a Propose to plug-back to 88 10615', then cement from 8 5-1/2" OD casing to 8800'	RULES A of 10,61 sulphur 800'. 5 8800 to , set re	AND REGULATIONS OF THE COMMISSION 15'. Drill stem test 10,565-10,61 water. No show of oil or gas. Will cement with 50 sacks, 10484 to 8931' with 50 sacks. Will run stainer and prepare to complete we eduction.	59
FOLLOW INSTRUCTIONS IN THE Drilled to a total depth of Recovered 2131' of black of Propose to plug-back to 80 10615', then cement from 5 5-1/2" OD casing to 8800' in the Fusselman sone for	RULES A of 10,61 sulphur 800'. 5 8800 to , set re	AND REGULATIONS OF THE COMMISSION 15'. Drill stem test 10,565-10,61 water. No show of oil or gas. Will cement with 50 sacks, 10484 to 8931' with 50 sacks. Will run stainer and prepare to complete we	59
FOLLOW INSTRUCTIONS IN THE Drilled to a total depth of Recovered 2131' of black a Propose to plug-back to 84 10615', then cement from 5 5-1/2" OD casing to 8800' in the Fusselman sone for	RULES A of 10,61 sulphur 800'. 5 8800 to , set re	AND REGULATIONS OF THE COMMISSION 15'. Drill stem test 10,565-10,61 water. No show of oil or gas. Will cement with 50 sacks, 10484 to 8931' with 50 sacks. Will run stainer and prepare to complete we eduction. Skelly Oil Company Company of Operator By	59
FOLLOW INSTRUCTIONS IN THE Drilled to a total depth of Recovered 2131' of black of Propose to plug-back to 80 10615', then cement from 5 5-1/2" OD casing to 8800' in the Fusselman sone for	RULES A of 10,61 sulphur 800'. 5 8800 to , set re	AND REGULATIONS OF THE COMMISSION 15'. Drill stem test 10,565-10,61 water. No show of oil or gas. Will cement with 50 sacks, 10484 to 8931' with 50 sacks. Will run stainer and prepare to complete we odustion. Skelly 011 Company Company of Operator Will of the state of	30 all
FOLLOW INSTRUCTIONS IN THE Drilled to a total depth of Recovered 2131' of black a Propose to plug-back to 84 10615', then cement from 5 5-1/2" OD casing to 8800' in the Fusselman sone for	RULES A of 10,61 sulphur 800'. 5 8800 to , set re	AND REGULATIONS OF THE COMMISSION 15'. Drill stem test 10,565-10,61 water. No show of oil or gas. Will cement with 50 sacks, 10484 to 8931' with 50 sacks. Will run stainer and prepare to complete we eduction. Skelly Oil Company Complex of Operator By Position Dist. Supt.	ell well to
FOLLOW INSTRUCTIONS IN THE Drilled to a total depth of Recovered 2131' of black of Propose to plug-back to 80 10615', then cement from 5 5-1/2" OD casing to 8800' in the Fusselman some for Approved	RULES A of 10,61 sulphur 800'. 5 8800 to , set re	AND REGULATIONS OF THE COMMISSION 15'. Drill stem test 10,565-10,61 water. No show of oil or gas. Will cement with 50 sacks, 10484 to 8931' with 50 sacks. Will run stainer and prepare to complete we eduction. Skelly Oil Company Company of Operator By Position Dist. Supt. Send communications regarding	ell well to

	BUILT A HOL COMMIDEION	1101110
4	uxpracept	Address
ľ	Oil & Gas Inspector	
1+		

.