

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

3-NMCC-HOBBS
1-R. J. STARRAK-TULSA
1-A. B. CARY-MIDLAND

1-ELB, ENGR.
1-FILE
1-BH, FIELD CLERK

Form C-103
Supersedes Old
C-102 and C-101
Effective 1-1-65

5a. Indicate Type of Lease
State ☒ Fee ☐
5. State Oil & Gas Lease No.
B-9312-5

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR INFORMATION TO OIL & GAS PRODUCERS OR FOR BACK TO A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT - FORM C-101, FOR OTHER PROPOSALS.)

1. ☐ OIL WELL ☐ GAS WELL ☐ OTHER ☒ Water Injection Well

2. Name of Operator
Getty Oil Company

3. Address of Operator
P. O. Box 730, Hobbs, New Mexico 88240

4. Location of Well
UNIT LETTER B 810 FEET FROM THE North LINE AND 2130 FEET FROM
THE East LINE, SECTION 5 TOWNSHIP 25S RANGE 33E N.M.P.M.

10. Field and Pool, or Wildcat
Dollarhide Tubb-Drinkar

15. Elevation (Show whether DF, RT, GR, etc.)
3159' DF

12. County
Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☐	OTHER ☒ Recemented casing

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

11-22-77 - Moved in and rigged up Western Wireline. Set Baker Model D pkr. at 5790'. Perforated 2-.41" holes - in 5 1/2" csg. at 3500'. Set DR plug in pkr.

11-23-77 - Ran Baker full bore pkr. on 2 3/8" tbq. and set at 5740'; tested to 3000#. Raised and set pkr. at 3270'. Howco cemented with 500 sxs Class "C" cement. Displaced cement to 3400'. WOC 24 hrs.

11-25-77 - Ran 4 3/4" bit and tagged cement at 3362'. Drilled cement 3362-3507'. Tested with 1000# for 30 mins. O.K.

11-29-77 - POH with tbq. & tools. Left seal assembly & anchor in Model D pkr. at 5790'. Welex ran & set another Model D pkr. at 5785', and ran new seal assembly; (185 jts. - 5774') tbq. set at 5785'. Rigged down and moved out. Placed well back on injection.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED David R. Crockett TITLE Area Superintendent DATE 1-25-79

Date R. Crockett

Orig. Signed by

John F. an

Geologist

APPROVED BY _____ TITLE _____ DATE JAN 29 1979

CONDITIONS OF APPROVAL, IF ANY: