

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-062368

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

West Dollarhide Dev. Unit

8. FARM OR LEASE NAME

9. WELL NO.

116

10. FIELD AND POOL, OR WILDCAT

Dollarhide Devonian

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 5, T25S, R38E

12. COUNTY OR PARISH 13. STATE

Lea

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR
GULF OIL CORPORATION

3. ADDRESS OF OPERATOR
P. O. Box 670, Hobbs, NM 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)
At surface

1980' FSL & 660' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3134' GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐
☐
☐
☐

PULL OR ALTER CASING

☐
☐
☐
☐

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☐
☐
☐

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)

☐
☐
☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

8485' PB.

POH. WIH tagged top of fish at 4804'. Recovered all of fish except 4 jts, Hydril, Seat nipple & mud anchor. With top of fish @ 8132', spotted 70 sx class "H" cmt from 8132' to 7500'. Rvrs hole. Set CIBP @ 7308'. (Could not go deeper) Ppd 170 sx class "H" cmt. Plug 7308' to 5808'. Pull bot tag to 5700'. Displaced hole w/10# brine abandonment mud. Check 9-5/8 - 5 1/2" pres found 120#. Bled dn in 30 sec w/1/2" steady water flow. Pres tested 5 1/2" csg to 500# for 30 min held ok. Perf 5 1/2" csg @ 3349-50' w/(4) 1/2" JH. Set pkr 3313' Circ out 5 1/2" - 9-5/8" annulus w/180 bbls 10# brine. Cmt rtnr set @ 3262. Pres test tbg to 3000# - held ok. Test 5 1/2" csg to 500# - ok. Establish circ up 9-5/8" - 5 1/2" csg annul Ppd 500 sx class "C" cmt w/6% gell w/friction reducer, followed w/175 sx class "C" neat. Circ out 30 bbls slurry to good cmt. CI 9-5/8" csg & sq to 1000#. Left 50' cmt on top of cmt rtnr. Rvrs hole. Spotted 50' plug to surface. Install well marker. Cleaned & cleared location.

Work performed 3/7/79 to 3/19/79.

RECEIVED

MAR 21 1979

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

N. P. Sikes, Jr.

TITLE

Area Engineer

DATE

3-19-79

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

APPROVED

JUL 30 1979

ACTING DISTRICT ENGINEER

O.C.D. HOBBS, OFFICE