

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLI
(Other instructions on
reverse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

OIL WELL ☐ GAS WELL ☒ OTHER ☐

NAME OF OPERATOR

Skelly Oil Company

ADDRESS OF OPERATOR

P. O. Box 1351, Midland, Texas 79701

LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

Unit Letter "J", 2310' FSL and 2310' FEL, Section 3-258-38E

PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3161' DF

5. LEASE DESIGNATION AND SERIAL NO.

MM-0301932

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

West Dollarhide Queen Sand Unit

8. FARM OR LEASE NAME

West Dollarhide Queen Sand Unit

9. WELL NO.

63

10. FIELD AND POOL, OR WILDCAT

Dollarhide Queen

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Section 3-258-38E

12. COUNTY OR PARISH

Lea

13. STATE

New Mexico

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

PULL OR ALTER CASING ☐

FRACTURE TREAT ☐

MULTIPLE COMPLETE ☐

SHOOT OR ACIDIZE ☐

ABANDON* ☐

REPAIR WELL ☐

CHANGE PLANS ☐

(Other) ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

REPAIRING WELL ☐

FRACTURE TREATMENT ☐

ALTERING CASING ☐

SHOOTING OR ACIDIZING ☐

ABANDONMENT* ☒

(Other) ☐

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

-) Moved in pulling unit 3-24-74. Pulled rods and tubing.
-) Set cast iron bridge plug at 3566' and capped with 25 sacks cement to 3436'.
-) Spotted 25 sacks cement plug 2600-2730', 100 sacks cement plug 1001-1521', and 10 sacks cement plug 11-64'.
-) Installed dry hole marker.

11 intervals not cemented were filled with 10.2# mud. No casing was pulled.
all plugged and abandoned 3-26-74.

I hereby certify that the foregoing is true and correct

SIGNED (Signed) D. R. CROW D. R. Crow TITLE Lead Clerk

DATE 4-10-74

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

APPROVED

JUL 14 1977

ARTHUR R. BROWN
DISTRICT ENGINEER

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

* GPO 782-930

JUL 1 1977
OIL CONSERVATION COMM.
HOBBS, N. M.