

To be attached to and be a part of -

New Mexico Oil Conservation Commission

Form C-105 covering record of Well #3 - State Lea No. 263 (Dated October 30, 1954)
Sec. 6-253-38E
Lea County, New Mexico.

RECORD OF PRODUCTION AND STIMULATION (Also, perforation intervals)

| <u>Perforations</u> | <u>Stimulation</u> | <u>Remarks</u> |
|----------------------------|---|--|
| <u>Holes</u> <u>Depth</u> | | |
| 180 6760-6805 | 1000 Gals. Mud acid & 3000 Gals. Regular) | Light show of oil gas on swabbing test; set Baker Model "K" bridging plug in 5-1/2" OD casing with 1 sack cement on top of plug at 6754' to plug back and plug off lower perfs. |
| 168 6705-6747 | 1000 Gals. Mud acid & 3000 Gals. Regular) | Swabbed 18 gals. oil per hour after acidizing |
| 156 6608-6642 | 1000 Gals. Mud acid & 3000 Gals. Regular) | Swabbed 3/4 BOPH after acidizing |
| 80 6570-6590 | 1000 Gals. Mud acid & 3000 Gals. Regular) | Swabbed 15 BO in 20 Hrs. after acidizing |
| 180 6465-6510 | 1000 Gals. mud acid & 3000 Gals. Regular & 6000 Gals. Regular) | Flowed 120 BO in 14 Hrs. thru 1/2" choke after last treatment. |
| 148 6382-6450, as follows: | | Flowed 66 BO in 6 hours after last treatment. |
| (24 6382- 6388 | 1000 Ga ls. Mud acid) | |
| (60 6408-6423 | 3000 Gals. Regular &) | |
| (40 6430-6440 | 7000 Gals. consisting) | |
| (24 6444-6450 | of 1000 Gals. Gel & 6000 Gals. Reg) | |

All perforations shown above are open at present except the perfs. from 6760' to 6805', which are below the bridging plug.

Potential: 206 BOPD based on 120 BO in 14 Hours.

October 30, 1954

Operator: Sinclair Oil & Gas Company

Address: 520 East Broadway, Hobbs, New Mexico

Name: CC Salter
C. C. Salter

Position
or Title District Superintendent