

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

JUL 16 1 05 PM '68

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State ☐ Fee ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Union Texas Petroleum Corporation	8. Farm or Lease Name Buffington "B"
3. Address of Operator 1300 Wilco Building, Midland, Texas 79701	9. Well No. 3
4. Location of Well UNIT LETTER M, 330 FEET FROM THE South LINE AND 330 FEET FROM THE West LINE, SECTION 19 TOWNSHIP 25-S RANGE 38-E N.M.P.M.	10. Field and Pool, or Wildcat Justis
11. Elevation (Show whether DF, RT, GR, etc.) 3066 DF	12. County Lea

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☒ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐ OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

The following remedial work is proposed:

- (1) Perforate Upper Tubbs-Drinkard - 1-1/2" Hole @ 5750, 5752, 5754, 5766, 5774, 5780, 5794, 5796, 5804, 5806. Total 10 holes.
- (2) Sand Frac W/3 - 10,000 Gal Gelled Brine Stages and 60,000 lbs - 20/40 Sand and Rock salt blocking agent. Thru 3 1/2" Frac tubing.
- (3) Perforate lower Blinbry and upper Blinbry W/1-1/2" hole @ 5556, 5569, 5594, 5628, 5654, 5661, 5678, 5693, 5696, 5704, 5706, 5124, 5136, 5142, 5166, 5173, 5176, 5183, 5217, 5236, 5242, 5256, 5270, 5274, 5278 - Total 25 holes
- (4) Sand frac W/4 - 20,000 gal gelled Brine Stages and 160,000 lbs - 20/40 Sand and Rock salt blocking agent through casing.
- (5) Set Model "D" pkr @ 5710 - run dual 2 3/8 tubing and place on production.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED R. W. Manry TITLE District Drilling Supt. DATE July 15, 1968

APPROVED BY John W. Kunyan TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: