




AREA 640 ACRES
LOCATE WELL CORRECTLY

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

15550 C.F. 000 000

WELL RECORD 7 IN 2 15

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE. If State Land submit 6 Copies

Anderson-Prichard Oil Corporation
(Company or Operator)

Buffington "B"
(Lease)

Well No. 3-D, in SW 1/4 of SW 1/4, of Sec. 19, T. 25S, R. 38E, NMPM.

Justin Tubb Pool, Lea County.

Well is 330 feet from South line and 330 feet from West line

of Section 19. If State Land the Oil and Gas Lease No. is

Drilling Commenced July 3, 1960 Drilling was Completed July 28, 1960

Name of Drilling Contractor John Drilling Company

Address Fort Worth, Texas

Elevation above sea level at Top of Tubing Head 3061 The information given is to be kept confidential until 19

OIL SANDS OR ZONES

No. 1, from 5822 to 5915 No. 4, from to

No. 2, from to No. 5, from to

No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.

No. 2, from to feet.

No. 3, from to feet.

No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	FEET AND PULLED FROM	PERFORATIONS	PURPOSE
13-3/8"	48	New	945	Guide			Surface
7"	20 & 23	New	5970	Guide		5822-5915	Production

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
17-1/2"	13-3/8"	945	800	Pump and Plug		
8-3/4"	7"	5970	1477	Pump and Plug		

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, and treated or shot.)

Acidized with 1000 gal mud acid

Result of Production Stimulation

Depth Cleaned Out

RECORD OF DRILL-STEM AND SPECIAL " " " "

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 5970 feet, and from feet to feet.
Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to Producing August 30, 1960

OIL WELL: The production during the first 24 hours was 155.87 barrels of liquid of which 100% was oil; % was emulsion; % water; and % was sediment. A.P.I. Gravity 39

GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of liquid Hydrocarbon. Shut in Pressure lbs.

Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy 925	T. Devonian	T. Ojo Alamo	
T. Salt 1030	T. Silurian	T. Kirtland-Fruitland	
B. Salt 2190	T. Montoya	T. Farmington	
T. Yates 2379	T. Simpson	T. Pictured Cliffs	
T. 7 Rivers	T. McKee	T. Menefee	
T. Queen	T. Lillenburger	T. Point Lookout	
T. Grayburg	T. Gr. Wash	T. Mancos	
T. San Andres	T. Granite	T. Dakota	
T. Glorieta 4750	T.	T. Morrison	
Blinberry 5110	T.	T. Penn	
T. Drinkard 5742	T.	T.	
T. Tubbs	T.	T.	
T. Abo	T.	T.	
T. Penn	T.	T.	
T. Miss	T.	T.	

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	115	115	Redbed				
115	1030	915	Redbed and Anhy				
1030	2190	1160	Anhy and Salt				
2190	2800	610	Lime				
2800	2975	175	Lime and Gyp				
2975	3596	621	Lime and Dolo				
3596	5748	2152	Lime				
5748	5970	222	Lime and Dolo				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

September 6, 1960

(Date)

Company or Operator Anderson-Prichard Oil Corp. Address Box 196, Midland, Texas

Name [Signature] Position or Title District Clerk

DST 5110-5220', open 2-1/2 hours, Rec 20' DF

AP 7 MI 2 15