NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

:	^	٠,	~
	ς.		,

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional

	Indicate Nature of Report by Chec	king Belo)W	· -
REPORT ON BEGINNING DRILLING OPERATIONS	REPORT ON RESULT OF TES OF CASING SHUT-OFF	T x	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL	REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	
	May 11,	1955	Hobbs, N. M	١.
Following is a report on the work	(Date) done and the results obtained under the h	eading no	ted above at the Buffington	
Velma Petroleum Cor	-	1	NW ^{se)} SW	19
25S 38E (Contract 1)	anglie Mattix		in the	
	May 5, 1955			
	(was not) obtained. LED ACCOUNT OF WORK DONE AND	RESUL	TS OBTAINED	
DETAIL an 105 joints, 3272, ith 200 sacks on bott ement set for 48 hour		, set	at 32804, cemented	
an 105 joints, 3272, ith 200 sacks on bott sement set for 48 hour to drop in pressure.	ED ACCOUNT OF WORK DONE AND 5-1/2* 14# J-55 casing on and 100 sacks on top	of R	at 32801, cemented dustler. A water for 30 min.	•
an 105 joints, 3272, ith 200 sacks on bott ement set for 48 hour o drop in pressure.	ED ACCOUNT OF WORK DONE AND 5-1/2* 14# J-55 casing om and 100 sacks on top and tested with 1000#	of R	at 32801, cemented dustler. I water for 30 min.	•
an 105 joints, 3272, ith 200 sacks on bott ement set for 48 hour to drop in pressure. Sid James	Velma Petroleum (Company) OMMISSION VALUE OF WORK DONE AND Series of the best of the b	cold	at 32804, cemented lustler. water for 30 min. Drilling Supt (Title)	
an 105 joints, 3272, ith 200 sacks on bott ement set for 48 hour o drop in pressure. Sid James Witnessed by	Jelma Petroleum Velma Petroleum (Company)	of R cold	at 32804, cemented lustler. water for 30 min. Drilling Supt (Title)	