

*									

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

WELL RECORD

DUAL COMPLETED

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE. If State Land submit 6 Copies

AREA 640 ACRES
LOCATE WELL CORRECTLY

Pan American Petroleum Corporation State AJ
(Company or Operator) (Lease)

Well No. 6, in SW 1/4 of SW 1/4, of Sec. 30, T. 25S, R. 38E, NMPM.
Justis Blinberry-Fusselman Pool, Lea County.

Well is 330 feet from South line and 330 feet from West line
of Section 30. If State Land the Oil and Gas Lease No. is E-497

Drilling Commenced 9-17-1960 Drilling was Completed 10-13-1960

Name of Drilling Contractor Davidson Drilling Company

Address 1004 Continental Life Bldg., Fort Worth 2, Texas

Elevation above sea level at Top of Tubing Head 3069' RDE. The information given is to be kept confidential until Not Confidential, 19

OIL SANDS OR ZONES

No. 1, from 5068' to 5778' No. 4, from to
No. 2, from 6820' to TD No. 5, from to
No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.
No. 1, from to feet.
No. 2, from to feet.
No. 3, from to feet.
No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
13-3/8"	35.6#-48#	New	320	Guide			Surface
9-5/8"	32.3#-36#	New	3211	Guide			Intermediate
7"	20#-23#	New	7065	Guide		5172-5330 6938-6954	Oil String

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
17"	13-3/8"	320	250	Pump Plug		
12-1/4"	9-5/8"	3200	250	Pump Plug		
8-3/4"	7"	7020	600	Pump Plug		

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Blinberry-Sand Fras, 20,000 gal. oil, 40,000# sand, 5172'-5330'

Fusselman-Acidized, 1,000 gal. 15%, 6938-54'

Result of Production Stimulation Blinberry - Flw 48 BO x 0 BW 24 hrs.

Fusselman - Flw 140 BO x 11 BW 18 hrs.

Depth Cleaned Out FSD-6986

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 7020 TD feet, and from feet to feet.
Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to Producing Fusselman 10-16-60
Blincyry 10-1-60, 19
Fusselman 18 hrs. 151
OIL WELL: The production during the first 24 hours was 46 barrels of liquid of which 23
was oil; 36% was emulsior; 7% water; and % was sediment. A.P.I.
Gravity 37

GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of
liquid Hydrocarbon. Shut in Pressure lbs.

Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy		T. Devonian	T. Ojo Alamo
T. Salt		T. Silurian	T. Kirtland-Fruitland
B. Salt		T. Montoya	T. Farmington
T. Yates	2340	T. Simpson	T. Pictured Cliffs
T. 7 Rivers		T. McKee	T. Menefee
T. Queen		T. Ellenburger	T. Point Lookout
T. Grayburg		T. Gr. Wash	T. Mancos
T. San Andres	3635	T. Granite	T. Dakota
T. Glorieta	4730	T.	T. Morrison
T. Drinkard	5962	T.	T. Penn
T. Tubbs	5778	T.	T.
T. Abo		T.	T.
T. Penn		T.	T.
T. Miss		T.	T.

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	70	70	Caliche				
70	918	848	Redbed				
918	1417	499	Anhy				
1417	2008	591	Anhy - Salt				
2008	2203	195	Anhy				
2203	2624	421	Anhy - Gyp				
2624	2728	104	Anhy				
2728	2824	96	Anhy - Gyp				
2824	3102	278	Anhy				
3102	3200	98	Anhy Lime				
3200	5160	1960	Lime				
5160	5255	95	Lime & Gyp				
5255	6959	1704	Lime				
6959	7020	61	Chert & Lime				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

November 3, 1960
Company or Operator Pan American Petroleum Corp. Address Box 68, Hobbs, New Mexico
Name Date Area Superintendent