

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE
(Other instructions
reverse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 0888

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal-Lowe

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Dublin-Devonian

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

7-26S-38E NMPH

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3,031' D.F.

12. COUNTY OR PARISH

Lee

13. STATE

N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

SUBSEQUENT REPORT OF:

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Approval is requested to plug this well that has been produced from Devonian formation through perforations at 9910-9865' since completion in July, 1960.

It is planned to fill hole with mud laden fluid and place 25 sack cement plug from PBTD of 9,916' to 9,695' covering oper perforations.

Attempt to part 5 $\frac{1}{2}$ " casing near 7,500' and place a 25 sack cement plug into stub of 5 $\frac{1}{2}$ " extending approximately 65' upward.

If successful in parting 5 $\frac{1}{2}$ " below top of Abo at 7,190', spot 25 sack plug extending from 7,190' to 7,124'.

Spot 25 sack plug in top of San Andres at 4,032' extending to 3,966'.

Place 25 sack cement plug from 3,966'-3,835' into bottom of 9-5/8" casing. SAN ANDRES.

Attempt to part 9-5/8" casing near 1,500' and spot 50 sack cement plug into stub extending approximately 67' upward.

If successful in parting 9-5/8" casing below top of salt (1550'-2050') spot a 50 sack cement plug extending from approximately 1,550' to 1,484'.

Spot 50 sack cement plug from 500' to 438'.

Place 10 sack cement plug in top 12' of 13-3/8" casing.

Weld steel plate on top of 13-3/8" casing and cement 4" regulation steel marker extending 4 feet above ground level with required data welded on it.

Location will be cleaned and leveled for inspection after work completed.

Oral approval to place plug from 9,916' to 9,865' obtained by telephone March 8, 1967. Other plugs to be placed after approval of application to plug.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Div. Production

DATE

March 8, 1967

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

APPROVED
MAR 9 1967
A. R. BROWN
DISTRICT ENGINEER

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.