
Form	9-331 a
(Fah	1951)



(SUBMIT IN TRIPLICATE)

'RIPLICATE)	Land Office
,	Lease No
STATES CE.OCC	Unit

GEOLOGICAL SURVEY

CE OF INTENTION TO DRILL		SUBSEQUENT	REPORT OF WATER SE	HUT-OFF	
CE OF INTENTION TO CHANGE F];		G OR ACIDIZING	
OF INTENTION TO TEST WAT		SUBSEQUENT		CASING	
E OF INTENTION TO RE-DRILL		SUBSEQUENT		ING OR REPAIR	
F OF The ENTION TO SHOOT OF		! !!		IMENT	
E OF INTENTION TO PULL OR					
CE OF INTENTION TO ABANDON	WELL	1 11			
(INDICA	ATE ABOVE BY CHECK M	MARK NATURE OF REPOR			
·				Anna na <i>m</i> adh	10
				July 25,	19
dersi-Lowe		(NDames		(Enhance	4
Noi is loca	ted 1990. fr	$\operatorname{rom}_{-} \left\{ \begin{array}{l} 1 \\ S \end{array} \right\}$ time an	d GG t. from	$\mathbf{m} \begin{bmatrix} \mathbf{E} \mathbf{x} \mathbf{x} \mathbf{x} \mathbf{x} \\ \mathbf{W} \end{bmatrix}$ time of sec	
	26-8	()	N.M.P.M.	• •	
1-1/4, Sec. 7 (½ Sec. and Sec. No.)	(Twp.)	(Range)	(Meridian)		
	Les			New Mexico	
 				(State or Territory)	
(Field)	-	unty or Bubdivision)			
(Field)	-		f t.	•	
(Field)	k floor above sea	a level is			
(Field)	k floor above sea	a level is	RK	in an indicate mudding jobs	cemal
(Field) elevation of the derric	k floor above sea	a level is	RK engths of proposed cast roposed work)		i, cemer
(Field) clevation of the derrich names of and expected depths 60 Set a Baker N Perforated 2 30 barrels fi with 1500 get flow, cleaned 122 bbis, oil	k floor above sea DE' to objective sands; sho ing points, and odel "N" Cl i builets per uid, 305 to ! ions acid. i to pit 40 m i, 2/10 of is	TAILS OF WOOD WAS SEEN, WEIGHTS, and led all other important pridge Plug a feet 1965 to 18 CGCA, flui Sumbod 16 bb. Inutes. Flow BSAW - Average poval in writing by the Coval	RK angths of proposed casi roposed work) † 9916' P.B.T 9910'. Swabb d level 8300' is of 75 bb! ad to tank !: ge GOR 1718/	"load plus Acidized "load", sterted hours, FTP-1400".	ı
(Field) Elevation of the derrick names of and expected depths 60 Set a Baker N Perforated 2 30 barrels fi with 1500 get flow, cleaned 122 bbis, oil	k floor above sea DE' to objective sands; sho ing points, and odel "N" Cl i builets per uid, 305 to i lons seid. i to pit 40 m i, 2/10 of is	TAILS OF WOOD WAS SEEN, WEIGHTS, and led all other important pridge Plug a feet 1965 to 18 CGCA, flui Sumbod 16 bb. Inutes. Flow BSAW - Average poval in writing by the Coval	RK angths of proposed casi roposed work) † 9916' P.B.T 9910'. Swabb d level 8300' is of 75 bb! ad to tank !: ge GOR 1718/	".D. led lead plus l. Acidized "lead", started hours, FTP=1400#.	ı