m 9- Feb. 1	- 331 a 951)	

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land Office	New Mexico
Lease No	0006

RECEIVED

JM7-1960

(ICO

THE OF INTENTION TO F	neil i	CURCEOUE	NT DEDOUT OF WATER CHIEF OFF		
	DRILLCHANGE PLANS	1	SUBSEQUENT REPORT OF WATER SHUT-OFF		
	TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING		
	RE-DRILL OR REPAIR WELL		NT REPORT OF RE-DRILLING OR REPAIR		
ICE OF INTENTION TO S		1 1	NT REPORT OF ABANDONMENT		
OTICE OF INTENTION TO PULL OR ALTER CASING			SUPPLEMENTARY WELL HISTORY		
OTICE OF INTENTION TO ABANDON WELL		34966	quent Report of Utili Stam		
	(INDICATE ABOVE BY CHECK	K MARK NATURE OF REPO	DRT, NOTICE, OR OTHER DATA)		
			June 6	. 19	
rel-Love	· 1 1 1980c.	APOOX.	3 660 tr Elim	7	
·		from $\left\{ \begin{array}{c} S \\ S \end{array} \right\}$ line as	nd ft. from $\{\stackrel{\Sigma}{W}\}$ line of se	ec	
(1/4 Sec. and Sec. No.)		(Range)	(Meridian)		
(14 sec. and sec. No.)	Loc	(Asiang)	New Mexico		
(Field)	(0	County or Subdivision)	(State or Territory)		
	depths to objective sands: s	how sizes, weights, and l	lengths of proposed casings; indicate mudding	z jobs, ceme	
names of and expected	ing points, a	nd all other important p	proposed work)		
	orili Stem Test f	d all other important p			
	orili Stem Test i 1 10,964° to li _p i	16 905' - 1,509'	water cushlan. Tool open		
	orili Stem Test i 1 10,964° to li,0	d all other important p	weter cushion. Tool open	ughout	
	orili Stem Test i 1 10,964° to li,0	16 105' - 1,509' Strong In 35 m	water cushion. Tool open limites and continued thro 1,500' water cushion, 5 g	ughout	
	orili Stem Test i 1 10,964' to li, on increased to a to gas to surface oli, and 180' b sec initial 20"	16 103' - 1,509' trong in 35 m Recovered lack suiphur w Sil.P. 36901	water cushion. Tool open limites and continued thro 1,500' water cushion, 5 g	ughout	
	ing points, a Orill Stem Test if 1 10,964' to li, if pur increased to a to gas to surfact oli, and 180' b initial 20' initial Fig.	16 103' - 1,309' trong in 35 m	water cushion. Tool open lightee and continued thro 1,500' water cushion, 5 gi later.	ughout	
	orili Stem Test i 1 10,964' to li, on increased to a to gas to surface oli, and 180' b sec initial 20"	PG 1,509' - 1,509' strong in 35 m s. Recovered lack suiphur w Sil.P. 36901 wing 7001 ng 7301	water cushion. Tool open lightee and continued thro 1,500' water cushion, 5 gi later.	ughout	
	orili Stem Test i 1 10,964° to li,0 m increased to a to gas to surface oli, and 180° bas initial 20° initial Flow Final Flowin	PG 1,509' - 1,509' strong in 35 m s. Recovered lack suiphur w Sil.P. 36901 wing 7001 ng 7301	water cushion. Tool open lightee and continued thro 1,500' water cushion, 5 gi later.	ughout	
	orili Stem Test i 1 10,964° to li,0 m increased to a to gas to surface oli, and 180° bas initial 20° initial Flow Final Flowin	PG 1,509' - 1,509' strong in 35 m s. Recovered lack suiphur w Sil.P. 36901 wing 7001 ng 7301	water cushion. Tool open lightee and continued thro 1,500' water cushion, 5 gi later.	ughout	
ne 2, 1960 - 5 interval Neck bid test. I gravity Pressure	ing points, a Orill Stam Test if 1 10,964° to li, if you increased to it to gas to surfact oli, and 180° bi es: initial 20° initial Figure Final Figure Final 50° S an of work must receive app.	16 16 105' - 1,309' 170ng in 35 m 1800 ming 7091 190 ming 7300 190 ming 730	water cushion. Tool open ilautes and continued throu i,500' water cushion, 5 gi rater.	ughout el. 43º	
ine 2, 1960 - 5 interval iteak bid test, 1 gravity Pressure	ing points, a Orill Stam Test if 1 10,964° to li, if you increased to it to gas to surfact oli, and 180° bi es: initial 20° initial Figure Final Figure Final 50° S an of work must receive app.	16 16 105' - 1,309' 170ng in 35 m 1800 ming 7091 190 ming 7300 190 ming 730	water cushion. Tool open lightes and continued throu 1,500° water cushion, 5 gi later.	ughout el. 43º	
ine 2, 1960 - 5 interval iteck bis test. I gravity Pressure understand that this pla	ing points, a Orill Stam Test if 1 10,964° to li, if you increased to it to gas to surfact oli, and 180° bi es: initial 20° initial Figure Final Figure Final 50° S an of work must receive app.	16 16 105' - 1,309' 170ng in 35 m 1800 ming 7091 190 ming 7300 190 ming 730	water cushion. Tool open ilautes and continued throu i,500' water cushion, 5 gi rater.	ughout el. 43º	
interval interval ineak bie test. gravity Pressure npany Fore	orili Stem Teet i 10,964' to li, 20 increased to a 10 ges to surface 11, and 180' b 12 initial 20' 12 initial Figure 13 Final Figure 13 Final Figure 13 Final Figure 14 Final Figure 15 Final Figure 16 Final Figure 17 Final Figure 18 Final Figure 18 Final Figure 18 Final Figure 18 Final Figure 19 Final Figure 19 Final Figure 10 Final Figure 11 Final Figure 12 Final Figure 13 Final Figure 14 Final Figure 15 Final Figure 16 Final Figure 17 Final Figure 18 Final Figure 18 Final Figure 19 Final Figure 19 Final Figure 10 Final Figure	16 16 105' - 1,309' 170ng in 35 m 1800 ming 7091 190 ming 7300 190 ming 730	water cushion. Tool open ilautes and continued throu i,500' water cushion, 5 gi rater.	ughout el. 43º	

U. S. GOVERNMENT PRINTING OFFICE 16-8437-5