UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land Office 1641	Mayico
Lease No. 14 112-	
Unit	

SUNDRY NO	TICES AND RE	PORTS ON WELLS
NOTICE OF INTENTION TO DRILL	SUBSPOUS	NT REPORT OF WATER SHUT-OFF.
NOTICE OF INTENTION TO CHANGE PLANS.	SUBSPOUR	NT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO TEST WATER SHI	UT-OFF. SUBSPOUF	NT REPORT OF ALTERING CASING.
NOTICE OF INTENTION TO RE-DRILL OR RE	PAIR WELL SUBSPOILE	NT REPORT OF REDRILLING OR REPAIR
LAGRICE OF INTENTION TO SHOOT OR ACIDI	ZE SIIRSFOILE	NT DEPORT OF ARABRAMENT
NOTICE OF INTENTION TO PULL OR ALTER	CASING SUPPLEME	NTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL.	X	NTARY WELL HISTORY
(INDICATE ABOV	VE BY CHECK MARK NATURE OF REPO	RT, NOTICE, OR OTHER DATA)
	J	March 27, 1951 , 19
Well No. 2 - Self is located	1980 ft. from $\binom{N}{S}$ line a	nd 660 ft. from E line of sec. 7
NW/4 (H Sec. and Sec. No.)	26S 38E	NMP
(H. Sec. and Sec. No.)	(Twp.) (Hange)	(Meridian)
nitucat	Lea	New Mexico
(Field)	(County or Subdivision)	(State or Territory)
The elevation of the derrick floor	above sea level is 3040	· f.
	above sea level is whenever	- 1 t.
	DETAILS OF WO	
(State names of and expected depths to objective sands; show sixes, weights, and lengths of proposed casings; indicate mudding jobs, camenting points, and all other important proposed work)		
This is to supplement our	enginest of Doc 20 3	roposed work)
for suspension of operation	The following or	.951, which approval was grented ork was done at that time plugged
back from total depth of 39	9861 to 37001 with a	ment. Filled hole with 10# mud
to 1340'. Set plus and come	ented to 13301 mile	ed 10 3/4" casing and filled with
10# mud to 10701, set plug	and used 50 ske came	d 10 3/4" casing and filled with
10# mud to 1070*, set plug and used 50 sks cement. Filled with 10# mud into surface pipe.		
	ta pluguing aparette	
We propose to complete plugging operations in the following manner. Place		
25 sks. cement in bottom of surface pipe which is set and cemented @ 603: Fill with heavy mud to top of surface pipe, place 10 sks cement at this point and		
cement cellar. Fill in c	filar and restore lo	cation to original condition as
near as possible.	011d1 dld 1030016 10	cation to original condition as
•		
I understand that this plan of work must re	ceive approval in writing by the Ge	plogical Survey before operations may be commenced.
Company RALPH LO		
Address Box 832	***************************************	•
Midland,	Texas	By / 72 / 12 / 12
Name	7	itle Agent

U. S. GOVERNMENT PRINTING OFFICE 16-8437-9