5. LEASE

Form 9-331 Dec. 1973

Form Approved. Budget Bureau No. 42-R1424

UNITED STATES
DEPARTMENT OF THE INTERIO
GEOLOGICAL SURVEY

FOR

JAMES A. GILLHAM

DISTRICT SUPERVISOR ee Instructions on Reverse Side

DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY	5. LEASE LC-050107(4) 6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	N/A 7. UNIT AGREEMENT NAME N/A 8. FARM OR LEASE NAME
1. oil gas other Water Inj. well	Mary E. Wills "A" 9. WELL NO.
2. NAME OF OPERATOR och Exploration Company, Div. of Koch Ind., Inc.	10. FIELD OR WILDCAT NAME Rhodes
3. ADDRESS OF OPERATOR P. O. Box 2256, Wichita, Kansas 67201 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 1135' FSL & 20' FWL AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 35-26S-37E 12. COUNTY OR PARISH 13. STATE Lea New Mexico
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	14. API NO. N/A 15. ELEVATIONS (SHOW DF, KDB, AND WD) GR 2979.28
REQUEST FOR APPROVAL TO: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON* (other) Plug & abandon SUBSEQUENT REPORT OF: SUBSEQUENT REPORT OF: OCT 14 U. S. GEOLOGI FARMINGTO	CAL SURVEY
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly statincluding estimated date of starting any proposed work. If well is different measured and true vertical depths for all markers and zones pertiner. Will be P & A as shown in the below	firectionally drilled, give subsurface locations and nt to this work.)*
 Top of cement behind 5-1/2" casing at 2700' Cast iron bridge plug set above perforation of cement on top of cast iron bridge plug. Will tag up on plug. 	s, (if any), with a minimum of 35'
 5-12/" casing will be shot off at 2700'. 100 foot plug (50 feet in and 50 feet out o salt formation. Will tag up on plug. 	f stub) then 100 foot plug at top of
5. 100 foot plug (50 feet in 50 feet out of sh plug at top of surface casing. Will tag up	
6. With a required surface dry hole marker.	
Subsurface Safety Valve: Manu. and Type	Set @ Ft.
18. I hereby certify that the foregoing is true and correct Assistant	
SIGNED CHARLES THE Operations Mg	r. DATE Oct. 7, 1980
(This space for Federal or State of	ffice use)
APPROVED CANES SEE SEE SEE SEE SEE SEE SEE SEE SEE	DATE

MAY 1 3 1000