

COPY TO O. C. G

Form 9-331  
Dec. 1973

Form Approved.  
Budget Bureau No. 42-R1424

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐

2. NAME OF OPERATOR  
CONOCO INC.

3. ADDRESS OF OPERATOR  
P. O. Box 450, Hobbs, N.M. 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 660' FNL & 660' FNL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

5. LEASE  
LC-030139 (6)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME  
NMFU

8. FARM OR LEASE NAME  
LANGLIE LYNN QUEEN UNIT

9. WELL NO.  
12

10. FIELD OR WILDCAT NAME  
LANGLIE MATTIX TRVRS. QN

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
SEC. 26, T-23S, R-36E

12. COUNTY OR PARISH  
LEA

13. STATE  
NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☒  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐

RECEIVED  
JUL 22 1980

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

U. S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Due to holes in csq. @ 580'-1300' we request approval to repair the csq. as follows: Run free pt. to determine where csq. is free (TDC @ 2100'). Back 4 1/2" csq. off at first collar above free pt. Strip 4 1/2" csq. out of hole. Run new 4 1/2", 9.5#, K-55 csq. in hole & screw into existing csq. POOH w/ RBP @ 3465'. Run production eqpt., landing SN @ 3682'. Return to production. No additional surface disturbance is required.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Wm A. Butterfield TITLE Administrative Supervisor DATE 7/18/80

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY:

USGS-5  
NMFU-4  
FILE

APPROVED

JUL 23 1980

DISTRICT SUPERVISOR

\*See Instructions on Reverse Side