



APPROVED

(SUBMIT IN TRIPLICATE)

SEP 3 1963

UNITED STATES

J. L. GORDON  
ACTING DISTRICT ENGINEER  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office

10-030130 (a)

Lease No.

Unit

## SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	X
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL	Completion Operations	X

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

C. M. Farnsworth "A" August 30, 1963

Well No. 9 is located 660 ft. from N line and 1662.2 ft. from E line of sec. 18

SE/4 SW/4, Sec. 18 T-26-S, R-37-E NMPM

(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)

Jalmit - Oil Lea New Mexico

(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 2971 ft. RDS

## DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

TD 3263. Ran logs. On 8-15-62, 5-1/2" OD 14# to 20# casing was run and set at 3263' with 200 ax cement and tested with 2000 PSI for 30 minutes. Test OK. Perforated 3215'-22' with 2 SPF. Acidized with 500 gal. On PT well pumped 72 BO x 88 BW in 24 hours. CGR 29°, GOR 528.

TD 3263'; PBD 3228'; TPay 3070'; Seven Rivers

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Pan American Petroleum Corporation

Address Post Office Box 68

Hobbs, New Mexico

By

Title Area Superintendent