



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office IC-030130 (a)
Lease No. _____
Unit _____

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL	Completion Operations	<input checked="" type="checkbox"/>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

C. H. Farnsworth "A" _____ August 30, 19 ⁶³
Well No. 9 is located 660 ft. from XXX line and 1662.2 ft. from XXX line of sec. 18
SE/4 SW/4, Sec. 18 T-26-S, R-37-E NMPM
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Jalmat - Oil Lea New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 2971 ft. RDB

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

TD 3263. Ran logs. On 8-15-62, 5-1/2" OD 14# to 20# casing was run and set at 3263' with 200 sx cement and tested with 2000 PSI for 30 minutes. Test OK. Perforated 3215'-22' with 2 SPF. Acidized with 500 gal. On PT well pumped 72 BO x 88 BW in 24 hours. CGR 29°, GOR 528.

TD 3263'; FBD 3228'; TPay 3070'; Seven Rivers

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Pan American Petroleum Corporation
Address Post Office Box 68
Hobbs, New Mexico
By _____
Title Area Superintendent

Original Signed by
S. STALL