

Form 3160-5
(June 1990)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED

Nov 20 8 46 AM '95

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

HAL J. RASMUSSEN OPERATING, INC.

3. Address and Telephone No.

310 W. WALL SUITE 906 MIDLAND, TX 79701 (915) 687-1664

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

SEC. 30, T26S, R37E UNIT I
1980' FSL & 660' FEL

5. Lease Designation and Serial No.

LC-030168B

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

EAVES B-1 NO-7

9. API Well No.

30-025-20106

10. Field and Pool, or Exploratory Area

SCARBOROUGH YATES-7 RIVERS

11. County or Parish, State

LEA COUNTY, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☒ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☒ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- 1) MIRU. POOH w/ RODS, TUBING, & PACKER.
- 2) RIH w/ CMT RETAINER & SET @ 2850'. Squeeze perf 2915-76'. Drill out sgs & TEST.
- 3) Drill out CIBP @ 3010'.
- 4) POOH w/ RBP @ 3130'.
- 5) RIH w/ CMT RETAINER & SET @ 3000'. Squeeze perf 3023-127'.
Drill out squeeze & TEST.
- 6) RIH w/ perf gun & CCL & perf @ 3108-3111'.
- 7) Acidize w/ 750 gallons 15% HCl.
- 8) RIH w/ rods & tubing & put on conventional pumping
UNIT DUE TO SMALL CASING SIZE.

RECEIVED
OCT 13 11 11 AM '94
GAC AREA

14. I hereby certify that the foregoing is true and correct

Signed Tyson L. Dunn Title PRODUCTION ENGINEER

Date 8/18/94

(This space for Federal or State office use)

Approved by Adam Salameh Title Petroleum Engineer

Date 11/7/94

Conditions of approval, if any: