Form	<b>9-331 a</b>
(Feb	. 1951)
_	



## (SUBMIT IN TRIPLICATE)

## UNITED STATES

## DEPARTMENT OF THE INTERIOR

Land Office	
Lease No.	LC-056927 A
Unit	

		PORTS ON WELLS
OTICE OF INTENTION TO DRILL		ENT REPORT OF WATER SHUT-OFF.
OTICE OF INTENTION TO CHANGE PLAN		ENT REPORT OF SHOOTING OR ACIDIZING
OTICE OF INTENTION TO TEST WATER S		ENT REPORT OF RE-DRILLING OR REPAIR
OTICE OF INTENTION TO RE-DRILL OR		ENT REPORT OF ABANDONMENT
OTICE OF INTENTION TO SHOOT OR AC OTICE OF INTENTION TO PULL OR ALTE	DIZE	IENTARY WELL HISTORY
OTICE OF INTENTION TO ABANDON WEL	IN CASHO	
(INDICATE A	ABOVE BY CHECK MARK NATURE OF RE	PORT, NOTICE, OR OTHER DATA)
		February 21 , 19 6
L Pago Natural Gas	1980 ft from [N] line	and 1650 ft. from $\frac{E}{E}$ line of sec. 13
	26 8 36 E	NMPM
(14 Sec. and Sec. No.)	(Twp.) (Range)	(Meridian)
Jalmat	Loa	New Mexico
(Field)	(County or Subdivision)	(State or Territory)
	DETAILS OF W	ORK
ate names of and expected depths to ob	DETAILS OF Works, and all other importants.	ORK  Id lengths of proposed casings; indicate mudding jobs, cemusit proposed work)
pudded 9:30 P.M. 1/9/6 5/8" new 24/ casing a ement circulated to su nd pressure tested cas 7/8" hole to 3371, to	DETAILS OF Working points, and all other imports:  33. Drilled 12 1/4"  15 374 with 275 eacks  17 arrange. Flug down 21  19 jung with 1,000 for jung down 21  10 jung down 3130 A.M.	ORK  Idlengths of proposed casings; indicate mudding jobs, cement proposed work)  Include to 374 feet and cemented regular plus 2% calcium chloride calcium chloride commutes. Test 0.K. Drilled 5 1/2* 15.5% J-55 casing at 3371 1/20/63. WOC 24 hours and press
pudded 9:30 P.M. 1/9/6 5/8" new 24/ casing a ement circulated to sw nd pressure tested cas 7/8" hole to 3371, to ith 175 sacks 4% gel. ested casing with 1,00	DETAILS OF Working points, and all other importations of the series of t	doller to 374 feet and cemented regular plus 2% calcium chloride. 30 P.M. 1/10/63. WOC 24 hours on inutes. Test 0.K. Drilled 5 1/2* 15.5% J-55 casing at 3371 1/20/63. WOC 24 hours and pressure 0.K.
pudded 9:30 P.M. 1/9/6 5/8" new 24/ casing a ement circulated to su nd pressure tested cas 7/8" hole to 3371, to ith 175 sacks 48 gel. ested casing with 1,00	DETAILS OF Weights, and ing points, and all other importants of the second of the seco	d lengths of proposed casings; indicate mudding jobs, cement proposed work)  hole to 374 feet and cemented regular plus 2% calcium chloride; 30 P.M. 1/10/63. WDC 24 hours; 30 minutes. Test O.K. Drilled; 5 1/2* 15.5% J-55 casing at 3371 1/20/63. WDC 24 hours and pressure to .K.
pudded 9:30 P.M. 1/9/6 5/8" new 24/ casing a ement circulated to sai nd pressure tested cas 7/8" hole to 3371, to ith 175 sacks 4% gel. ested casing with 1,00	DETAILS OF Working points, and all other importations of the series of t	d lengths of proposed casings; indicate mudding jobs, cement proposed work)  hole to 374 feet and cemented regular plus 2% calcium chloride; 30 P.M. 1/10/63. WDC 24 hours; 30 minutes. Test O.K. Drilled; 5 1/2* 15.5% J-55 casing at 3371 1/20/63. WDC 24 hours and pressure to .K.
pudded 9:30 P.M. 1/9/6 5/8w new 24/ casing a ement circulated to sw and pressure tested case 7/8w hole to 3371, to ith 175 sacks 4% gel. ested casing with 1,00  I understand that this plan of work a company Bogle Farms, ddress e/o 0il Report	DETAILS OF Weights, and ing points, and all other importants of the second of the seco	doller to 374 feet and cemented regular plus 2% calcium chloride 30 P.M. 1/10/63. WOC 24 hours 30 minutes. Test 0.K. Drilled 5 1/2* 15.5% J-55 casing at 3371 1/20/63. WOC 24 hours and press est 0.K.
pudded 9:30 P.M. 1/9/6 5/8" new 24 casing a sement eirculated to su and pressure tested cas 7/8" hole to 3371, to ith 175 sacks 4% gel. ested casing with 1,00  I understand that this plan of work n ompany Bogle Farms, ddress e/o Oil Report	DETAILS OF Well- plective sands; show sizes, weights, are ing points, and all other importants.  3. Drilled 12 1/4"  at 374 with 275 sacks arface. Plug down 21; sing with 1,000 for stal depth. Cemented Plug down 3:30 A.M.  bod for 30 minutes, to the formulation of the control	d lengths of proposed casings; indicate mudding jobs, cement proposed work)  hole to 374 feet and cemented regular plus 2% calcium chloride; 30 P.M. 1/10/63. WDC 24 hours; 30 minutes. Test O.K. Drilled; 5 1/2* 15.5% J-55 casing at 3371 1/20/63. WDC 24 hours and pressure to .K.