

DEC 1962

		X	

E. W. STANLEY
DISTRICT ENGINEER

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYLand Office New MexicoLease No. NM-021422Unit B

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	X
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

December 3, 1962

19

Shell-Federal BE
Well No. 1 is located 660 ft. from [N] line and 1650 ft. from [E] line of sec. 4
NW/4 NE/4, sec. 4 24 S 34 NNPM
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Wolverine area wildcat Lea New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 3567 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Ran 11,990' of 9-5/8" (40#, 43.5# & 47#, R-90 & P-110) casing and cemented 12,005' with 1000 sacks Class C plus 45 gal (1st stage), and 1250 sacks Class C plus 128 gal plus 1 cu.ft./sack Stratocrete "6" (2nd stage). Plug down (1st stage) @ 6:05 p.m. (MST), November 18, 1962. Plug down (2nd stage) @ 11:15 p.m. (MST), November 18, 1962. After 82 hours, tested with 2000 psi for 30 minutes - no pressure drop.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Shell Oil CompanyAddress Box 1858Roswell, New MexicoBy W. R. GreeneTitle Acting Division Mech. Engr.