

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPI (TE+
(Other instructions re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

10-032604 (a)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Government H

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Salant11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA**Sec. 29-T26S-37E**

12. COUNTY OR PARISH

Lea

13. STATE

New Mexico

1.

OIL ☐ GAS ☐
WELL WELL OTHER **Dry Hole**

2. NAME OF OPERATOR

Cities Service Oil Company

3. ADDRESS OF OPERATOR

P.O. Box 69, Hobbs, New Mexico

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)

At surface

660' FSL & 660' FWL of Sec. 29-T26S-37E Lea County, New Mexico

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

2947 DF

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☒(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

The above well was plugged in the following manner:

1. A 25 sack cement plug was set on top of ret. @ 3169' to 2868'.
2. The 4 1/2" csg. was shot off @ 2590' and a 40 sack cement plug was set @ 2650' to 2502' (60' below and 88' above csg. stub).
3. A 40 sack cement plug was set @ 1300' to 1170'.
4. A 40 sack cement plug was set @ 800' to 670'.
5. A 40 sack cement plug was set @ 450' to 320'.
6. 8-5/8" CD csg. set @ 395 w/300 sacks was left in place.
7. A bridge was set in the 8-5/8" csg. 20' below surface and was filled to surface w/a 7 sack cement plug w/a 3" pipe marker extending 4' above ground to indicate a dry hole.
8. The location has been cleared of all debris, pits have been levelled and cellar filled in a workman like manner.
9. This location is now ready for inspection.

18. I hereby certify that the foregoing is true and correct

SIGNED

A. Robertson

TITLE

District Clerk

DATE

12-8-64

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.