

9-19-64

- cont. -

18' dns shly anhy dolo; 8' sli friable
sd., appears to be water sd; 1½' shly sd.,
w/good stain; 4½' shly sd., w/NS.
Cored 3568-3622', rec 54' being:
3' shly sd., w/NS; 4' sd., w/sli to fair
bldg oil; 3' sd., w/NS; 3½' dns shly dolo;
1/2' shl; 15' dns shly dolo; 7' dns sdy dolo;
9' dolomitic sd., w/NS; 5½' sd., w/scatt fair
bldg oil; 3½' tight sd., w/NS.
DST (7-R) 3740-3800', open 3 hrs,
GTS in 38 mins,
Flwd to pits for 22 mins;
Flwd 2 hrs,
Rec 14 bbls salty sul wtr (cut 10% heavy oil)

9-26-64

rev out 14 B Salty Sul Wtr (cut 10% heavy oil)
1 hr ISIP 1331#, FP 246-464#,
2 hr FSIP 1311#.
TD 4212', running 9 5/8" casing.

10-5-64

DST 4012-4212', open 1 hr,
rec 3010' black sul wtr,
1 hr ISIP 1439#, FP 123-1439#,
2 hr FSIP 1439#.
TD 4212', PBD 3833', COMPLETED
Perf 3733-41', 3743-47' W/4 SPF
Ac. 500 gals (MA)

