

COUNTY	LEA	FIELD Undesignated	STATE NM
OPR	SKELLY OIL COMPANY		
	3 Hobbs "Q"	MAP	
	Sec. 16, T-24-S, R-36-E		
	660' fr S Line & 1980' fr W Line of Sec.	CO-ORD	
	Spud 12-11-64		
	Temp Abd. 1-23-65	CLASS	EL 3382
CSG & SX - TUBING	FORMATION	DATUM	FORMATION DATUM
	LOG:		
8 5/8" 353' 250	Anhy 1680		
5 1/2" 3850' 200	B/Salt 3364		
	Yates 3546		
	7-R 3772		
LOGS EL GR RA IND HC A			
	TD 3850', PBD 3642'		

TEMPORARILY ABANDONED

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Hondo Drilg. Co. PROP DEPTH 3900' TYPE

12-19-64 F.R. 12-17-64; Oper's Elev. 3389' Df
PD 3900' - Seven Rivers
Contractor - Hondo Drilg. Co.
Coring @ 3819'.
Cored 3675-3733', rec 56½' being:
2' sd., w/good stn & odor; 2' shly sd., w/NS;
2' dns dolo; 1' gry sh; 3' dns dolo; 2' dolo
sd., w/scatt shows; 5' shly dolo sd., w/NS;
10' dns anhy dolo; 3' shly sd., w/NS; 2' dns
dolo; 2' shly sd., w/NS; 2' dolo sd., w/scatt
shows; 2' dolo sd., w/NS; 1' dns dolo; 1' shly
sd., w/NS; 2' dns dolo; 4' dolo sd., w/NS; 2'
dns dolo; 1' dolo sd., w/NS; 6' dns dolo., w/NS;
1½' dns anhy dolo., w/good vuggy poro & oil stn.

12-19-64 - cont. -

Cored 3733-91', rec 58' being:
1' dolo., w/NS; 1' shly sd., w/NS;
1' shly sd., w/show oil; 5' shly sd.,
w/NS; 7½' dns shly dolo; 4½' dns dolo.,
w/scatt vugs & oil stn; 2' shly dolo., w/NS;
6½' shly sd., w/show 3756-57'; 1' dns dolo.,
w/oil stn; 3½' silty sd., w/NS; 3' dns dolo.,
w/NS; 6½' shly sd., w/NS; 1½' silty sd., w/
oil stn; 4' shly sd., w/½' show; 10' dns
dolo., w/NS.

12-28-64

TD 3850', PBD 3832', swbg load.
Cored 3791-3850', rec 59' being:
14' dolo., shly w/scatt vugs & scatt bldg
oil; 3' sd., wet; 1½' dolo., w/scatt vugs,

NS; 3½' sd., wet; 10' dolo., shly, scatt
vugs, wet; 27' dolo., w/scatt vugs, few strks
of bldg oil & sul odor.

Perf 3786-93' W/2 SPF

Ac. 250 gals.

Swbd 3 BAW & swbd dry

Frac 10,000 gals oil + 10,000# sd. 3786-93'.

Swbd 27 BLO in 10 hrs.

Perf 3798-3800', 3802-04' W/2 SPF

Ac. 250 gals. 3798-3804'

Swbd 29 BLO & AW in 3 hrs.

1-9-65

TD 3850', PBD 3777', pmpg load.

Swbd 38 BFW + 2 BLO in 10 hrs from 3786-3804'.

Squeezed perfs 3786-3804' W/65 sx.

Perf 3766-69' W/2 SPF

Ac. 250 gals.,

Could not break down.

1-9-65

- cont. -

Ac. 500 gals.

Frac 10,000 gals oil + 7900# sd. 3766-69'.

Swbd 8 BLO + 8 BFW in 2 hrs.

Perf 3662-71' W/2 SPF

Set BP@ 3704'

Ac. 250 gals. 3662-71'

Swbd dry.

Frac 10,000 gals oil + 10,000# sd. 3662-71'.

Flwd 77 BLO in 14 hrs & died, no gas.

Pulled BP @ 3704'

1-16-65

Pmpd 13 BLO + 72 BFW in 24 hrs 3662-3769'.

TD 3850', PBD 3777', pmpg load.

1-23-65

Pmpd 3 BLO + 65 BFW in 24 hrs 3662-3769'.

TD 3850', PBD 3642', TEMPORARILY ABANDONED.

Pmpd 3 BLO + 67 BFW in 24 hrs (3662-3769')

Squeezed perfs 3662-3769' W/250 sx.

Set Pkr @ 3642'

Perf 3607-12', 3618-27' W/2 SPF

Ac. 250 gals. 3607-27'

Swbd dry

(Holding for tcps)

2-1-65

TD 3850', PBD 3642', Completion Reported.

(Holding for salt water disposal)