

IP Seven Rivers Perfs 2993-3154' Flwd 223 BOED, Pot. Based on
24 hr test thru 5/16" chks. IP 400-600#, gravity 35. GOR
2677.

CONT.	PROP	DEPTH	TYPE
DATE		1300'	

P.R. 9-30-65
PB 3300' - R
10-18-65 Drilg. 2865' unhy.
10-25-65 ID 3280', prep to test.
Cored 2980-3068', rec 88' sd. & drilg. w/18.9'
sd., w/good show; 18.8' sd., w/sli. to fair sh.
Cored 3068-3158', rec 90' sd. & drilg. w/6.1'
dolo., w/sli show; 6.0' dolo. & fair
good show; 6.1' sd., w/fair to g. d show.
Cored 3158-3231', rec 73' sd. & dolo., w/29.5'
sli show.
Cored 3231-80', rec 49' sd. & drilg. w/17.2'
sd., w/sli show; 27.5' dolo., w/good per.
bidg oil & wlr.
Perf @ 2991', 2995', 3005', 3053', 3059'
3154' W/1 SPV
At 1500 gals.
Prod 60,000 gals oil + 84,500# sol.

LEA Jalmat NM
CONTINENTAL OIL CO., #10 Eaves B-1

Sec. 31-263-31E
Page #2

11-1-65 TD 3280', tstg.
Recovered load.
Fwd 64 BC in 8 hrs thru 5/16" chk.
11-8-65 TD 3280', WO Potential.
11-15-65 TD 3280', COMPLETED
LOG TOPS: Base Salt 2766', Yates 2936',
Seven Rivers 3252'.