Form 9-331
(May 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

JUL 27 4 13 PM '65

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL [X] GAS WELL [ ] OTHER

2. NAME OF OPERATOR: Pan American Petroleum Corp.

3. ADDRESS OF OPERATOR: Box 68 Hobbs, N.M. 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.)
At surface
920' FNL x 497' FWL, Sec 7 (Unit D, NW/4 NW/4)

5. LEASE DESIGNATION AND SERIAL NO.: LC 030180-B b

6. IF INDIAN, ALLOTTEE OR TRIBE NAME:

7. UNIT AGREEMENT NAME:

8. FARM OR LEASE NAME: C.M. FARNSWORTH "B"

9. WELL NO.: 6

10. FIELD AND POOL, OR WILDCAT: JALMAT (OIL)

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA: 7-26-37 NMPM.

12. COUNTY OR PARISH: LEA

13. STATE: NM

14. PERMIT NO.:

15. ELEVATIONS (Show whether DF, RT, GR, etc.): 2965' RDB.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:				SUBSEQUENT REPORT OF:			
TEST WATER SHUT-OFF	[ ]	PULL OR ALTER CASING	[ ]	WATER SHUT-OFF	[X]	REPAIRING WELL	[ ]
FRACTURE TREAT	[ ]	MULTIPLE COMPLETE	[ ]	FRACTURE TREATMENT	[ ]	ALTERING CASING	[ ]
SHOOT OR ACIDIZE	[ ]	ABANDON*	[ ]	SHOOTING OR ACIDIZING	[ ]	ABANDONMENT*	[ ]
REPAIR WELL	[ ]	CHANGE PLANS	[ ]	(Other) Completion			[X]
(Other)							

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD-2970'. On 7/5/65, 5½" OD 14# H-40 Casing was set at 2970' w/ 150 sx Inco x ½# Tuff Plug per sx. Tested casing w/ 1500 psi for 30 minutes. Test O.K. Perforated interval 2947-52 w/ 2JSPF. Acidized w/ 500 gal.

On PT, well pumped 39 BO x 457 BW in 18 hrs. Gr. 29.6°. GOR-NA.

18. I hereby certify that the foregoing is true and correct

SIGNED Original Signed V. L. STALEY TITLE Area Supt DATE 7-19-65

(This space for Federal or State office use)

APPROVED BY ________ TITLE ________ DATE ________
CONDITIONS OF APPROVAL, IF ANY:

APPROVED
JUL 2_ 1965
J. L. GORDON
ACTING DISTRICT ENGINEER

OGJ
04-USGS
1-JSG
1-JSGP
1-GLS

*See Instructions on Reverse Side