

COUNTY	LEA	FIELD	Scarborough	STATE	NM
OPR	PAN AMERICAN PETROLEUM CORP.				MAP
	8 Farnsworth, C. M. "B"				
	Sec. 7, T-26-S, R-37-E				CO-ORD
	990' FNL & 1657' FWL of Sec.				
	Spd 9-27-65		CLASS		
	Cmp 12-13-65	FORMATION	DATUM	FORMATION	DATUM
CSG & SX - TUBING					
8 5/8"	349'	200			
5 1/2"	3056'	150			
LOGS EL GR RA IND HC A					
		TD 3058', PBD 3044'			

IP Lower Yates 3032-36' Pmpd 11 BOPD + 987 BW. Pot. Based on 24 hr test, gravity 29.6, GOR 980.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT.	Cactus	PROP DEPTH	3350'	TYPE
DATE				

F.R. 9-23-65; Opr's Elev. 2970' KB
PD 3350' - Seven Rivers
Contractor - Cactus

10-4-65 TD 3056', prep to perf.
8 5/8" casing @ 349' W/200 sx.
5 1/2" casing @ 3056' W/150 sx.

10-11-65 TD 3058' (Corr.), PBD 3056', RU Pump.
Perf 3050-54' W/2 SPF
Ac. (3050-54') 200 gals.,
Swbd & Flwd 5 BO, 75 BLW + 46 BNW/17 hrs.
Re-Ac. (3050-54') 750 gals.
Swbd 21 BO, 91 BLW + 343 BNW/30 hrs.

10-18-65 TD 3058', PBD 3056', tstg.
Pmpd 631 BW/72 hrs.

10-25-65 TD 3058', PBD 3044', tstg.
Set CI Retainer @ 3044'
Squeezed perfs 3050-54' W/150 sx.

25-65 Continued
 Perf 3032-36' W/2 SPF
 Ac. (3032-36') 250 gals.,
 Swbd 74 BLW + 36 BNW/9 hrs.
 Flwd 20 BW/48 hrs thru 24/64" chk.
11-1-65 TD 3058', PBD 3044', tstg on pump.
 Re-Ac. (3032-36') 750 gals.
 Pmpd 14 BO + 65 BW/48 hrs.
11-8-65 TD 3058', PBD 3044', tstg on pump.
 Re-Ac. (3032-36') 2500 gals.
 Pmpd 12 BO + 74 BLW/24 hrs.
11-15-65 TD 3058', PBD 3044', tstg.
 Pmpd 21 BO + 84 BW/72 hrs.

11-22-65 TD 3058', PBD 3044', pmpg load.
 Pmpd 1 BO + 11 BW/29 hrs.
 Frac (3032-36') 7500 gals wtr + 1100# sd.
11-29-65 TD 3058', PBD 3044', tstg on pump.
 Pmpd 62 BLW + 1303 BNW/120 hrs.
12-6-65 TD 3058', PBD 3044', tstg on pump.
 Pmpd 1007 BW/24 hrs, w/scum of oil.
12-13-65 TD 3058', PBD 3044', tstg on pump.
 Pmpd 9 BO + 1027 BW/24 hrs.
12-20-65 TD 3058', PBD 3044', COMPLETED.
 LOG TOP: Yates 2800'.