

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.
LC-030180(a)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL ☒ WELL GAS ☐ WELL OTHER ☐

2. NAME OF OPERATOR

3. ADDRESS OF OPERATOR

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

330' FNL X 1659.9' FWL, Sec. 18, (UNIT C, NE 1/4 NW 1/4)

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

C.M. FARNSWORTH "A"

9. WELL NO.

10. FIELD AND POOL, OR WILDCAT

JALMAT - OIL
11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

18-26-37 N.M.P.M.

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, OR, etc.)

2967' R.D.B.

12. COUNTY OR PARISH

LEA

13. STATE

N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

T.D. 3318; Ram logs. On 9-15-65, 5 1/2" OD 14" H40 Casing
was set at 3318' w/ 270 sy Incon plus 1/2" #14
Tuf Plug. Tested casing w/ 1800 psi for 30
minutes. Test O.K. Perf. 3204-08 1/2 SPF. Acidized
w/ 200 gal. Dry. Unable to squeeze. Set BP @ 3170' and
capped w/ 15' Cement. (PBD-3155) Perforated 3535-38 1/2 SPF.
Acid. w/ 200 gal. Dry. Squeezed w/ 150 sy cement below retainer
set at 3100' (PBD) Perforated 3041-45 1/2 SPF. Acidized
w/ 700 gallons.

On PT, well pumped 38 B0 X 10 B74 in 24 hours. GOR 2284,
Cgr. 29.6°.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Area Supt

DATE

9- - 65

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

APPROVED

OCT 8 1965

J. L. GORDON
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side

0-4-USGS
1-JWB
1-SUSP
1-WIS