Form 9-331 Dec. 1973 Form Approved. Budget Bureau No. 42-R1424

5. LEASE LC-050107**(d)** 

## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

FOR

JAMES A. GILLHAM \*See Instructions on Reverse Side

GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME N/A
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different	7. UNIT AGREEMENT NAME N/A
reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME
1. oil gas other Water Inj. well	Mary E. Wills "A"  9. WELL NO.
2. NAME OF OPERATOR	12
och Exploration Company, Div. of Koch Ind., Inc.	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	Rhodes
P. O. Box 2256, Wichita, Kansas 67201	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)	Sec. 35-26S-37E
AT SURFACE: 30' FSL & 2537 FWL	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL:	Lea New Mexico
AT TOTAL DEPTH:	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	N/A
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) GR 2982'
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	7
TEST WATER SHUT-OFF	
SHOOT OR ACIDIZE	FIVED   DEGELVEIN
REPAIR WELL REC	
PULL OR ALTER CASING	(NOTE: Report results of multiple completion or zone
MULTIPLE COMPLETE $\Box$ $\Box$ / $0C_{\perp}$	1 4 1000
CHANGE ZOINES	LL S. GEOLOGICAL SURVE
(other) Plug & abandon U. S. GE	OLOGICAL SURVEY U. S. GEOLOGICAL SURVEY MINGTON, N. M. HOOBS, NEW MEXICO
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly statincluding estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine Will be P & A as shown in below states.	directionally drilled, give subsurface locations and int to this work.)*
. Top of cement behind 5-1/2" casing at 2200'.	
. Cast iron bridge plug set above perforations,	(if any), with a minimum of 35'
of cement on top of cast iron bridge plug. Fi	
Will tag up on plug.	
5-1/2" casing will be shot off at 2200'.	
. 100 foot plug (50 feet in and 50 feet out of ${ m s}$	stub) then 100 foot plug at top of
salt formation. Will tag up on plug.	
. 100 foot plug (50 feet in, 50 feet out of show	
plug at top of surface casing. Will tag up or	plug.
. With a required surface dry hole marker.	
Subsurface Safety Valve: Manu, and Type	Set @ Ft.
18. I hereby certify that the foregoing is true and correct Assistar	
SIGNED AMPLICATIONS A TITLE Operations A	Mgr. DATE Oct. 7, 1980
APPROVED(This space for Federal or State of	office use)
APPROVED BYS. SELT PETER W. CHESTER TITLE CONDITIONS OF APPROVAL, IF ANY:	DATE
MAY 5 1081	