5. LEASE

LC-050107(a)

Form 9-331 Dec. 1973 Form Approved. Budget Bureau No. 42-R1424

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
DEPORTS ON WELLS	N/A 7. UNIT AGREEMENT NAME
SUNDRY NOTICES AND REPORTS ON WELLS	N/A
Do not use this form for proposals to drill or to deepen or plug back to a different eservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME
1. oil gas	Mary E. Wills "A"
1. oil gas other Water Inj. well	9. WELL NO.
2. NAME OF OPERATOR	13
ch Exploration Company, Div. of Koch Ind., Inc.	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	Rhodes
P. O. Box 2256, Wichita, Kansas 67201 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
below.)	Sec. 35-26S-37E
AT SURFACE: 1259' FNL & 2183' FWL	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	Lea New Mexico
	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	N/A
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	GR 2986'
TEST WATER SHIT OFF	
FRACTURE TREAT	CEIVED DECEIVE
REPAIR WELL	T (NOTE Report results of multiple completion or zone 1 1 1 Property of 1880)
PULL OR ALTER CASING OUT	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
CHANGE ZONES	STOLOGICAL SURVEY
ABANDON* 🔼 📙 \ FAF	MINGTON, N. M. U. S. GEOLOGICAL SURV
(other) Plug & abandon	HODDS, NEW MEXICO
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly starting including estimated date of starting any proposed work. If well is a measured and true vertical depths for all markers and zones pertine Will be P & A as shown in below s	directionally drilled, give subsurface locations and nt to this work.)*
1. Top of cement behind 5-1/2" casing at 2160'	•
2. Cast iron bridge plug set above perfortions	, (if any), with a minimum of 35'
of cement on top of cast iron bridge plug.	Fill hole with 9.5# salt type mud.
Will tag up on plug.	
3. 5-1/2" casing will be shot off at 2100'.	
4. 100 foot plug (50 feet in and 50 feet out o	f stub) then 100 foot plug at top
salt formation. Will tag up on plug.	5 . 1 5
5. 100 foot plug (50 feet in and 50 feet out o	
cement plug at top of surface casing. Will	tag up on plug.
6. With a required surface dry hole marker.	
Subsurface Safety Valve: Manu. and Type	Set @ Ft.
18. I hereby certify that the foregoing is true and correct Assistant	
SIGNED	gr. DATE October 7, 1980
ABBOVED	#
APROVED is space for Federal or State of	πice use;
APPROVED CONDITIONS OF APPROVAL IF AND W. CHESTER TLE	DATE
MAY 5 1981	

JAMES A. GILLHAM DISTRICT SUPERVISOR Instructions on Reverse Side