

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

N.M. Oil Corp
P 1980
Hobbs, NM 88241

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT-" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☐ Gas Well ☒ Other WIW

2. Name of Operator

PLAINS PETROLEUM OPERATING COMPANY

3. Address and Telephone No.

415 W. WALL, SUITE 1000 MIDLAND, TX 79701 915/683-4434

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1300' FSL & 1300' FWL, Sec. 35 (M), T23S, R37E

5. Lease Designation and Serial No.
NM LC064118

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Eva E. Blinbry #13

9. API Well No.

30-025-21697

10. Field and Pool, or Exploratory Area

Langlie Mattix 7 Rvrs Queen GB

11. County or Parish, State

LEA, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other

☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

12-4-97 SNG Well P&A Services, LLC set 4-1/2" cement retainer @ 3350'. Squeeze w/75 sx "C" cement @ 2 BPM @ 600 psi. Unstung & cap w/20' cement. TOC @ 3330'.

Circulate hole w/55 bbls 10# mud.

Spot 20 sx "C" cement from 1600' to 1310'.

Spot 10 sx "C" cement from 900' to 800'.

Spot 20 sx "C" cement from 382' to 92'.

Spot 20 sx "C" cement from 60' to surface.

Cut off wellhead 4' below ground level. Install Dry Hole Marker.

BLM's Patricia Hutchings witnessed.

Approved as to plugging of the well bore
Liability under bond is retained until
surface restoration is completed.

14. I hereby certify that the foregoing is true and correct

Signed

Bonnie Husband

Title Admin. Assist.

Date 12/16/97

(This space for Federal or State office use)

Approved

(ORIG. SGD.) ALEXIS C. SWOBODA


Title

PETROLEUM ENGINEER

Date

DEC 22 1997

Conditions of approval, if any:



PM DEC 17 A 11: 04

NEWELL, N.H.
NEWELL OFFICE