

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE\*  
(Other instructions on reverse side)Form approved.  
Budget Bureau No. 42-R1424.  
5. LEASE DESIGNATION AND SERIAL NO.NM-040763 UNIT B  
6. IF INDIAN, ALLOTTEE OR TRIBE NAME

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT" for such proposals.)1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

HUMBLE OIL &amp; REFINING COMPANY

3. ADDRESS OF OPERATOR

Box 1600, MIDLAND, TEXAS 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface660' FNL, 1980' FEL OF NE 1/4 OF SEC. 20, T-24-S,  
R-36-E, LEA COUNTY, NEW MEXICO

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3381 DF

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

FEDERAL DAVISON A

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

WILDCAT

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

SEC. 20, T-24-S, R-36-E

12. COUNTY OR PARISH

LEA

13. STATE

NEW MEXICO

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

WELL PLUGGED AND ABANDONED (THIS FORM SUPPLEMENTS FORM 9-331

SUBMITTED ON 8-17-66)

SET THE FOLLOWING PLUGS:

SET CEMENT RETAINER AT 14,400'

PLUG #5 - SQUEEZE CEMENTED FROM 14,578 TO 14,310 W/80 SX CMT.

PLUG #6 - FROM 10,080 TO 9,946 W/50 SX CMT.

PLUG #7 - FROM 5,900 TO 5,713 W/90 SX CMT.

LAST PLUG ON BOTTOM AT 3:00 P.M. 9-30-66.

WELL TURNED OVER TO U.S.G.S. WATER RESOURCES DIVISION  
FOR WATER OBSERVATION AS PREVIOUSLY REQUESTED.

18. I hereby certify that the foregoing is true and correct

SIGNED

A. L. Clemmer

TITLE

AGENT

DATE

10-3-66

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

APPROVED

DEC 8 1967

\*See Instructions on Reverse Side

J. L. GORDON  
ACTING DISTRICT ENGINEER