

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
B-228	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER		7. Unit Agreement Name
2. Name of Operator Ernest A. Hanson		8. Farm or Lease Name Ramsay State
3. Address of Operator P. O. Box 1515, Roswell, New Mexico		9. Well No. 1
4. Location of Well UNIT LETTER <u>A</u> <u>330</u> FEET FROM THE <u>North</u> LINE AND <u>330</u> FEET FROM THE <u>East</u> LINE, SECTION <u>12</u> TOWNSHIP <u>26-S</u> RANGE <u>36-E</u> NMPM.		10. Field and Pool, or Wildcat Scarborough
15. Elevation (Show whether DF, RT, GR, etc.) 2965' KB		12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Commence drilling @ 11:30 P.M. on April 21, 1966.
Total Depth 342' red beds.
Ran 330' of 8-5/8", 24#, H-40 casing to 342' (measured from KB) w/225 sx.
Incor cement w/2% CaCl + 2% gel. Circulate approximately 20 sacks of
cement to surface. W.O.C. 12 hours. Pressure tested casing to 600
p.s.i. for 30 mins. No leaks. Prepare to drill ahead.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Ernest A. Hanson TITLE Explor. Mgr. DATE 4-23-66

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY: