

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPL
(Other instructions
verse side)

B*
re

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

L.C. 030168 b

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Continental Oil Company

3. ADDRESS OF OPERATOR

Box 460, Hobbs, New Mexico

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface

**660' FNL and 660' FWL, Sec. 31, T-26S, R-37E,
Lea County, New Mexico, NMFM**

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

2935 DF

7. UNIT AGREEMENT NAME

N.M.F.H.

8. FARM OR LEASE NAME

Eaves B-1

9. WELL NO.

12

10. FIELD AND POOL, OR WILDCAT

NMFU

Scarborough Yates Seven Rivers

11. SEC., T., R., E., or S.E., and SURVEY OR AREA

Sec. 31, T-26S, R-37E

12. COUNTY OR PARISH 13. STATE

Lea

N. M.

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled to T. D. 3350' (Yates Sand). Ran GR & Sonic logs. Ran 101 jts. (3277') 4 1/2" 9.5# J-55 casing w/10 centralizers and 20 scratchers. Set at 3277', cemented w/80 sx. Class "C" cement w/4% G&I and 11# salt per sack. Plug down @ 7:15 p.m., October 29, 1966. Top of cement @ 2700'.

APPROVED

NOV 2 1966

**J. L. GORDON
ACTING DISTRICT ENGINEER**

18. I hereby certify, that the foregoing is true and correct

SIGNED

W. L. Smith

TITLE **Staff Supervisor**

DATE **11-1-66**

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

USGS (5) PAN AM. (2) Atl. Ros. (2) Calif.-Midland (3) File

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment, data on any former or present productive zones, on other zones with present significant fluid contents not sealed off by cement or otherwise, depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1963-O-685229
867-851

Las County, New Mexico, 479M
650: 2MI and 660: 2MI, 200, 31, T-202, R-378

Box 400, Hobbs, New Mexico
Continental Oil Company

Drilled to T. D. 3350' (Water Sand). Ran 10' of 1 1/2" casing w/10 cement
101 lbs. (3277') 4 1/2" 9.25 1-25 casing w/10 cement
casing. Set at 3277' cemented w/80 ex. Case "10"
and 1 1/2" salt per sack. Plug down @ 1:15 P.M., 10/1/63
of cement @ 2700'.