

COUNTY	IEA	FIELD	Scarborough	STATE	NM
OPR	CONTINENTAL OIL COMPANY				MAP
	12	Eaves B-1			
	Sec. 31. T-26-S, R-37-E				CQ-ORD
	660' FNL, 660' FWL of Sec.				MN 21862
	Spd 10-20-66				
	Cmp 11-12-66				CLASS
		FORMATION	DATUM	FORMATION	DATUM
CSG & SX - TUBING					
7 5/8" 409'	200				
4 1/2" 3277'	80				
LOGS EL GR RA IND HC A					
	TD 3277';				
IP Yates Perfs 3172-3250' Pmpd 41 BOPD + 80 BW. Pot. Based on 24 hr test, gravity 29.3.					

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Roy Smith	PROP DEPTH 3300'	TYPE
DATE		

F.R. 9-15-66
 PD 3300' - Yates-Seven Rivers
 Contractor - Roy Smith
 10-24-66 Drlg. 2905' lm.
 10-31-66 TD 3277', WOC.
 Cored 3049-3101', rec 52' dolo., w/sli scatt shows.
 Cored 3101-50', rec 49' dolo & sd., w/sli scatt bldg oil & wtr.
 Cored 3150-3202', rec 52' dolo., w/scatt poro & shows.
 Cored 3202-52', rec 42' dolo & sd., w/scatt shows.
 Cored 3252-77', rec 23' dolo & sd., w/scatt poro & show.

11-7-66 TD 3277'; SE.
 Perf @ 3172', 3183', 3188', 3216', 3225',
 3236' W/1 SPI
 Acid (3172-3236') 3000 gals.
 Swbd 9 EO + 6 EW/5 hrs & swbd dry (3172-3236')
 Acid (3172-3236') 5000 gals.
 Swbd & Flwd 14 ELO + 7 PAW/10 hrs
11-14-66 TD 3277', pmpg load.
 Flwd 1½ EO in 1 hr, TP 10-12# (3172-3236')
 Perf @ 3172', 3183', 3188', 3216', 3225',
 3236', 3243', 3250' W/1 SPI
 Acid (3172-3250') 5000 gals.
 Fmpd 46 ELO + 18 EW/18 hrs.
11-21-66 TD 3277', COMPLETE.
 LOG TOP: Yates 3000'.