

UNITED STATES
DEPARTMENT OF THE INTERIOR

SUBMIT IN TRIPLE
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

GEOLOGICAL SURVEY OF THE U.S.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or deepen a well in a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER		5. LEASE DESIGNATION AND SERIAL NO. LC 062384
2. NAME OF OPERATOR Tenneco Oil Company		6. LAND INDIAN, ALIEN, OR TRIBE NAME
3. ADDRESS OF OPERATOR Box 1031 Midland, Texas		7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 660' FSL & 660' FSL, Section 14, T-26-S, R-37-E N		8. FARM OR LEASE NAME Leonard Federal
14. PERMIT NO.		9. WELL NO. 2
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 2986' DF		10. FIELD AND POOL, OR WILDCAT Jalant (Yates Gas)
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 14, T-26-S R-37-E
		12. COUNTY OR PARISH Lea
		13. STATE N. Mex.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐	WATER SHUT-OFF ☒	REPAIRING WELL ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐	FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐	SHOOTING OR ACIDIZING ☒	ABANDONMENT* ☐
REPAIR WELL ☐	CHANGE PLANS ☐	(Other) ☐	

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded @ 11:30 a.m. 10-15-66. Drilled 9-7/8" hole to 400'. Set 7" 20# J-53 casing @ 400'. Cemented w/120 sx Class C w/4% gel plus 50 sx Class C w/2% CaCl₂ thru shoe. Cement did not circulate. Cemented thru 1" pipe w/80 sx Class C w/2% CaCl₂ & brought cement to surface. Cement in place @ 7:30 a.m. 10-16-66. After WOC for 18 hours, tested casing w/1000 drilled 6-1/4" hole to 3100'. Ran logs. Set 4-1/2" 10.5# J-55 @ 2701'. Cemented w/50 sx Class C w/2% 16% Gel & 3% salt, plus 50 sx Class C w/2% CaCl₂. Plug down @ noon. 12-22-66. Top of cement by temp survey 1250'. Drilled cement and shoe and washed to bottom. Treated open hole 2701 - 3100 w/2000 gals. mud acid.

18. I hereby certify that the foregoing is true and correct

SIGNED BY J. F. CARNES **J. F. Carnes** TITLE **Dist. Prod. Eng.** DATE **Nov. 10, 1966**

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____

CONDITIONS OF APPROVAL, IF ANY:

APPROVED

NOV 14 1966

*See Instructions on Reverse Side

J. L. GORDON
ACTING DISTRICT ENGINEER

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1963-O-685229
867-851

NOV 12 11 08 AM '63
HOBBS OFFICE O.C.C.