

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease  
State  Fee

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator <b>Samedan Oil Corporation</b>	8. Farm or Lease Name <b>Hughes "B-4"</b>
3. Address of Operator <b>2207 Wilco Building, Midland, Texas 79701</b>	9. Well No. <b>12</b>
4. Location of Well UNIT LETTER <b>A</b> , <b>660'</b> FEET FROM THE <b>North</b> LINE AND <b>660'</b> FEET FROM THE <b>East</b> LINE, SECTION <b>18</b> TOWNSHIP <b>23-S</b> RANGE <b>37-E</b> NMPM.	10. Field and Pool, or Wildcat <b>Langlie-Mattix</b>
15. Elevation (Show whether DF, RT, GR, etc.) <b>3331' G. L.</b>	12. County <b>Lea</b>

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK

TEMPORARILY ABANDON

PULL OR ALTER CASING

OTHER \_\_\_\_\_

PLUG AND ABANDON

CHANGE PLANS

SUBSEQUENT REPORT OF:

REMEDIAL WORK

COMMENCE DRILLING OPNS.

CASING TEST AND CEMENT JOB

OTHER Installation of artificial lift equipment.

ALTERING CASING

PLUG AND ABANDONMENT

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Nolan Brunson, Inc. set and assembled OCS "Duck" Type Twin Crank pumping Unit and 7 1/2" x 10" Type C M Ajax gas engine on portable cement base. Eunice Well Service rigged up, ran fishing tool on sand line and retrieved Bumper spring and standing valve. Ran 2" x 1 1/4" x 16' H-F Sub-surface pump, 1 - 2' x 5/8" rod on sub on top of pump, 128 - 5/8" x 25' and 19 - 3/4" x 25' sucker rods and 1 1/4" x 16' polished rod. Connected well head started well pumping on 14 - 36" strokes per minute. Seating nipple is at 3695'.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED G.W. Putnam TITLE Division Prod. Supt. DATE April 2, 1968

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY: