2							
NO. OF COPIES RECEIVED	<u> </u>						
SANTA FE	NEW MEXICO OIL CONSERVATION COMMISSION				Form C-101 Revised 1-1-65		
FILE				ſ	5A. Indicate	Type of Lease	
U.S.G.S.					STATE		
LAND OFFICE					5. State Oil	& Gas Lease No.	
OPERATOR					K-5366		
					TIIIII		
APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK							
1a. Type of Work						ement Name	
b. Type of well					8, Farm or L	ease Name	
OIL X GAS WELL OTHER SINGLE X MULTIPLE ZONE ZONE ZONE				ZONE	Spear State		
Doyle Hartman 3. Address of Operator							
						10. Field and Pool, or Wildcat	
312 Midland National Bank Bldg. Midland, Texas 79701					Undesignated		
4. Location of Well UNIT LETTER F LOCATED FEET FROM THE North LINE					1111111	<i>XHIHHHHHH</i>	
1000	Maat	^					
AND 1980 FEET FROM	THE West LIN	E OF SEC.	WP. 265 RGE. 37	L NMPM	12. County		
					Lea		
\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	<i>++++++++++++++</i> ++++++++++++++++++++++	*********	*******	HHHHH	TEG	<i>44444441</i> 777	
//////////////////////////////////////	444444447	1 <i>4////////////////////////////////////</i>	9. Proposed Depth	19A. Formation	111111	20. Rotary or C.T.	
Λ			3750'			Rotary	
21. Elevations (Show whether DF,	<i>RT</i> , etc.) 21A. Kind	nd & Status Plug. Bond 21B. Drilling Contractor		1 011 001		. Date Work will start -	
3013 G.L.	Filed	& Approved	Pool Compa	anv		27, 1975	
23.		ROPOSED CASING AND					
	· · · · · · · · · · · · · · · · · · ·	· · · · · · · · · · · · · · · · · · ·	·· j · · · · · · · · · · · · · · · · ·	1			
SIZE OF HOLE	SIZE OF CASING	WEIGHT PER FOOT			CEMENT	EST. TOP ,	
* 8-3/4"	<i>L</i>	20#	293'	65			
<u>b=1/4</u>	4-1/2"	10.92#	3750'	200		2000	
l. Re-enter.	drill out cer	hent nlugs	 and clean out		 ainel	total	
1. Re-enter, drill out cement plugs, and clean out to original total depth of 3000'.							
2. Deepen well to new T.D. of 3750'.							
3. Run electric logs and perform any other necessary open-hole testing.							
4. Run and ce	ement 4-1/2" d	casing.					
	ther a Queen-			or a Jai	lmat-Ya	tes	
gas completion, depending on well data.							
(3000 psi double-ram BOP will be used to facilitate blow-out protection)							
(DELENG CONNENCED)							
					5-4-	75	
				EXPIRES -	-		
	ROPOSED PROGRAM: IF I	PROPOSAL IS TÔ DEEPEN O	R PLUG BACK, GIVE DATA O	N PRESENT PRO	DUCTIVE ZONE	AND PROPOSED NEW PRODUC-	
I hereby certify that the information	on above is true and comp	lete to the best of my kr	nowledge and belief.				
Signed Anthere !!	Schmidt		r-Part Owner	. annt	- Date Ja	n. 13. 1975	
(This space for Sense User							
APPROVED BY A CAMER TITLE UPERVISOR AND AND TO DATE							
CONDITIONS OF APPROVAL, TE	ANY:	.) 		<u> </u>	JATE		
, , , ,	John Yuronka	a on May 6,	1967			/	