

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN DUPLICATE

(See other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R355.5.

5. LEASE DESIGNATION AND SERIAL NO.

LC-045701

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal "H"

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Langlie Mattix

11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA

Sec. 18, T-23-S, R-37-E

12. COUNTY OR PARISH

Lea

13. STATE

New Mexico

1a. TYPE OF WELL:

OIL WELL

☒

GAS WELL

☐

DRY

☐

Other

b. TYPE OF COMPLETION:

NEW WELL

☒

WORK OVER

☐

DEEP-EN

☐

PLUG BACK

☐

DIFF. RESVR.

☐

Other

2. NAME OF OPERATOR

Amerada Petroleum Corporation

3. ADDRESS OF OPERATOR

P. O. Box 668 - Hobbs, New Mexico 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)*

At surface

1980' FNL & 660' FEL of Section 18

At top prod. interval reported below

At total depth

14. PERMIT NO.

DATE ISSUED

15. DATE SPUDDED

8-30-67

16. DATE T.D. REACHED

9-6-67

17. DATE COMPL. (Ready to prod.)

9-13-67

18. ELEVATIONS (DF, RKB, RT, GR, ETC.)*

3337' DF

19. ELEV. CASINGHEAD

20. TOTAL DEPTH, MD & TVD

3775'

21. PLUG, BACK T.D., MD & TVD

3769'

22. IF MULTIPLE COMPL., HOW MANY*

23. INTERVALS DRILLED BY

ROTARY TOOLS

CABLE TOOLS

Rotary

24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)*

25. WAS DIRECTIONAL SURVEY MADE

26. TYPE ELECTRIC AND OTHER LOGS RUN

Penrose - Perfs. 3590' to 3735'

27. WAS WELL CORED

No

28. COMPENSATED FORMATION DENSITY

CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
9-5/8"	25.4#	331'	12-1/4"	250 sz.	None
5-1/2"	15.5#	3774'	7-7/8"	300 sz.	None

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
					2-3/8"	3611'	

31. PERFORATION RECORD (Interval, size and number)

One hyper jet shot at: 3590', 3603', 3606', 3611', 3628', 3631', 3637', 3640', 3671', 3676', 3689', 3692', 3695', 3699', 3716' & 3735'.

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
3590' to 3735'	250 gals. 15% NE acid; 8000 gals. treated wtr. & 8000# sand; 29,000 gals. gelled brine wtr. & 29,000# sand.

33.*

PRODUCTION

DATE FIRST PRODUCTION		PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump)					WELL STATUS (Producing or shut-in)	
9-13-67		Pump					Producing	
DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROD'N. FOR TEST PERIOD	OIL—BBL.	GAS—MCF.	WATER—BBL.	GAS-OIL RATIO	
9-24-67	24		→	27	31	69 Load	1166	
FLOW. TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE	OIL—BBL.	GAS—MCF.	WATER—BBL.	OIL GRAVITY-API (CORR.)		
		→				35		

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)

Vented

TEST WITNESSED BY

B. A. Moore

35. LIST OF ATTACHMENTS

Compensated Formation Density Log

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED

TITLE District Superintendent

DATE 10-6-67

*(See Instructions and Spaces for Additional Data on Reverse Side)

INSTRUCTIONS

General: This form is designed for submitting a complete and correct well completion report and log on all types of lands and leases to either a Federal agency or a State agency, or both, pursuant to applicable Federal and/or State laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office. See instructions on items 22 and 24, and 33, below regarding separate reports for separate completions.

If not filed prior to the time this summary record is submitted, copies of all currently available logs (drillers, geologists, sample and core analysis, all types electric, etc.), formation and pressure tests, and directional surveys, should be attached hereto, to the extent required by applicable Federal and/or State laws and regulations. All attachments should be listed on this form, see item 35.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 18: Indicate which elevation is used as reference (where not otherwise shown) for depth measurements given in other spaces on this form and in any attachments. **Items 22 and 24:** If this well is completed for separate production from more than one interval zone (multiple completion), so state in item 22, and in item 24 show the producing interval, or intervals, top(s), bottom(s) and name(s) (if any) for only the interval reported in item 33. Submit a separate report (page) on this form, adequately identified, for each additional interval to be separately produced, showing the additional data pertinent to such interval.

Item 29: "Sacks Cement": Attached supplemental records for this well should show the details of any multiple stage cementing and the location of the cementing tool. **Item 33:** Submit a separate completion report on this form for each interval to be separately produced. (See instruction for items 22 and 24 above.)

37. SUMMARY OF POROUS ZONES:				38. GEOLOGIC MARKERS	
SHOW ALL IMPORTANT ZONES OF POROSITY AND CONTENTS THEREOF; CORED INTERVALS; AND ALL DRILL-STEM TESTS, INCLUDING DEPTH INTERVAL TESTED, CUSHION USED, TIME TOOL OPEN, FLOWING AND SHUT-IN PRESSURES, AND RECOVERIES		DESCRIPTION, CONTENTS, ETC.		NAME	MEAS. DEPTH
FORMATION	TOP	BOTTOM			TRUE VERT. DEPTH
Queen (Penrose Sand)	3580'	3775'	Samples not examined. No DST's run. Poor to fair porosity indicated by Formation Density Log.	Santa Rosa Sd. Dewey Lake Rustler Salado B/Salado Yates B/Yates 1st. 7 Rivers 2nd. 7 Rivers Queen Penrose Sd.	642' 900' 1161' 1287' 2564' 2704' 2828' 2995' 3281' 3440' 3580'