

Form 3160-5
(June 1990)

"CORRECTED"
FROM REPORT SUBMITTED 3-31-98
UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

N.M. Oil & Gas Division
P.O. Box 1980
Hobbs, NM 88241

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT-" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Doyle Hartman

3. Address and Telephone No.

P. O. Box 10426, Midland, TX 79702 (915) 684-4011

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FNL, 660' FEL (H)
Section 7, T-23-S, R-37-E

5. Lease Designation and Serial No.
LC-0350556B

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Stevens B #21

9. API Well No.

30-025-22287

10. Field and Pool, or Exploratory Area

Langlie Mattix (7-R-Q)

11. County or Parish, State

Lea Co., NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment ✓
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

3-25-98 - 4-1/2" casing did not pass casing integrity test.

3-26-98 - Joe Laura approved P&A.

3-30-98 - Run 49 joints of 2-3/8" tubing to 1522' mixed and pumped 50 sx of Class C cement down 2-3/8" tubing. Pull 25 joints of 2-3/8" tubing. Mix and pump 50 sx of Class C cement. Cement circulated to surface. Pulled 13 joints of 2-3/8" tubing. Pump cement down 2-3/8" tubing and fill 4-1/2" casing to surface. Total 110 sx cement.

~~3-31-98~~ - Cut off wellhead and install dry hole marker. This well is now plugged and abandoned. Witnessed by Steve Caffey with BLM.

14. I hereby certify that the foregoing is true and correct

Signed [Signature]

Title Engineer

Date 05/06/98

(This space for Federal or State office use)

Approved by (ORIG. SGD.) GARY GOURLEY

Title PETROLEUM ENGINEER

Date JUN 10 1998

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side