

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE
(Other instructions on
reverse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ Recomplete as Water Supply Well		5. LEASE DESIGNATION AND SERIAL NO. LC 03087
2. NAME OF OPERATOR Gulf Oil Corporation		6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR P. O. Box 980, Kermit, Texas 75745		7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 660' from South Line and 2130' from East Line		8. FARM OR LEASE NAME C. E. LaMunyon
14. PERMIT NO. Dated 4-2-70		9. WELL NO. 31
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3294' DF		10. FIELD AND POOL, OR WHOLE CAT Teague Blinguey
		11. SEC. T. R. & M. OR BLM. AND SURVEY OR AREA 22-23-37E
		12. COUNTY OR PARISH 13. STATE Loa New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
(Other) ☐

PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
ABANDON* ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF

WATER SHUT-OFF ☐
FRACTURE TREATMENT ☐
SHOOTING OR ACIDIZING ☐
(Other) ☒ **Recomplete as water well.**

REPAIRING WELL ☐
ALTERING CASING ☐
ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting and proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Set wire line bridge plug in 5-1/2" OD casing at 5465'.
Dumped 2 sacks cement on top with dump bailer. Plug back total depth 5448'. Perforated San Andres 4546-48', 4472-74', 4423-25', 4362-64', 4275-77' and 4207-09' with 2 JHPT. Ran tubing with packer to 4011', acidized with 3,000 gallons BDA with 1-1" ball sealer every 120 gallons. IR 4.6 BPM @ 2100 psi. Swabbed 225 BW in 7 hrs., fluid level 1500', static 600'. Ran 60 HP Reds pump on 2-7/8" OD IPC tubing to 2025'. Well tested 2592 BHD on 4-27-70.

18. I hereby certify that the foregoing is true and correct

SIGNED ORIGINAL SIGNED BY: H. F. SWANNACK
(This space for Federal or State office use)

TITLE Area Production Manager

DATE April 23, 1970

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

ACCEPTED FOR RECORD

APR 30 1970

*See Instructions on Reverse Side

U.S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conducted for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1983 O-885229

GPO 8 37-499

507-851

