

UNITED STATES
DEPARTMENT OF THE INTERIOR

SUBMIT IN TRIPPLICATE
(Other instructions
verse side)

Form approved.
Budget Bureau No. 42-R1424.

GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐		5. LEASE DESIGNATION AND SERIAL NO. Federal LC 030187	
2. NAME OF OPERATOR Gulf Oil Corporation		6. IF INDIAN, ALIOTTIE OR TRIBAL NAME	
3. ADDRESS OF OPERATOR P. O. Box 980, Kermit, Texas		7. UNIT AGREEMENT NAME	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 460' FNL and 1980' FWL		8. FARM OR LEASE NAME C. E. Lammyon	
14. PERMIT NO.		9. WELL NO. 35	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3294' RKB		10. FIELD AND POOL, OR WILDCAT Teague Blinebry	
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 27-23S-37E	
		12. COUNTY OR PARISH 13. STATE Lea New Mexico	

18. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☒

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

It is proposed to set bridge plug at 5400' and perforate Upper Blinebry from 5352-54', 5403-05' and 5474-76' with 4 - 1/2" JEFF. Acidize perforations with 3,000 gallons of 7-1/2% NEA with 1 - 1" RCN ball sealer every 120 gallons down tubing. Pull tubing, frac down 5-1/2" OD casing with 21,000 gallons gelled brine, 27,000 lbs. 20-40 mesh sand in 3 stages of 1,000 gallons pad, 6,000 gallons gel brine with 1-1/2 ppg. Stages to be separated with 500 gallons 15% NEA and 3 - 1" ball sealers. Work to start on approval.

18. I hereby certify that the foregoing is true and correct

SIGNED

C. E. Fidler

TITLE

Area Engineer

DATE

MAY 2, 1969

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

APPROVED

MAY 5 1969

ARTHUR K. BROWN
DISTRICT ENGINEER

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1983-O-685229