

COUNTY LEA FIELD Teague STATE NM 30-025-22608

OPR GULF OIL CORP. MAP

40 LaMunyon, C. E.

Sec. 21, T-23-S, R-37-E

CO-ORD

660' FNL, 2180' FWL of Sec.

Spd 6-6-68

Cmp 7-10-68

CLASS

E

CSG & SX - TUBING

8 5/8" 922' 356

5 1/2" 6300' 510

LOGS EL GR RA IND HC A

FORMATION

DATUM

FORMATION

DATUM

TD 6300', PBD 6261'

IP Blinebry Perfs 5550-5832' Pmpd 128 BOPD + 42 BW. Pot. Based on 24 hr test, GOR 7464, Gravity 39.1.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Cactus Drlg. Co.

PROP DEPTH 6300'

TYPE RT

DATE

F.R. 6-20-68; Elev. 3322' KB

PD 6300' - Blinebry

Contr. - Cactus

6-14-68

Drlg. 4298' 1m.

6-24-68

Drlg. 6287'.

7-1-68

TD 6300', PBD 6261', RU Pump

Perf 5550-52', 5605-07', 5688-90', 5778-80',
5830-32' W/4 SPF

Acid (5550-5832') 500 gals 15%

Frac (5550-5832') 35,000 gals wtr + 45,000#
sd. + 2000 gals 15%

Swbd 65 BLW in 2 hrs (-861 BLW)

7-8-68

TD 6300', PBD 6261', pmpg load.

7-15-68

TD 6300', PED 6261', COMPLETE

LOG: Glor 4943', Blinebry 5336'

30-025-22608

COUNTY	LEA	FIELD	Teague	STATE	NM	OWWO
OPR	GULF OIL CORP.					
	40 La Munyon, C. E.					
	Sec 21, T-23-S, R-37-E					
	660' FNL, 2180' FWL of Sec.					
	CLASS				EL	
	Re-Cmp 2-1-69	FORMATION	DATUM	FORMATION	DATUM	
CSG & SX - TUBING						
8 5/8" at 922' w/356 SX						
5 1/2" at 6300' w/510 SX						
LOGS EL GR RA IND HC A	TD 6300'; PED 6261'					
IP (Blinebry) Perf 5376-5832' F 102 BOPD + 120 BW. Pot based on 24 hr test thru 14/64" chh, GOR 6471, Grav 40.2, CP 1550#, TP 1200#						

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. PROP DEPTH 5505' TYPE WO
DATE

3-19-69 F.R.C. 3-21-69; Opr's Elev. 3319' DF
PD 5505' WO (Blinebry)
(Orig. comp. 7-10-68 thru Perfs 5550-5832',
OTD 6300', OPB 6261')
TD 6300'; PED 6261'; COMPLETE
Perf 5376-78', 5422-24', 5466-68',
5503-05' w/4 SPF
Acid (5376-5505') w/4000 gals
Attempted to Frac (5376-5505')
Re-Perf 5376-68', 5422-24', 5466-68',
5503-05' w/4 SPF
Acid (5376-5505') 4000 gals (7½%)
Frac (5376-5505') 6000 gals wtr + 9000# sd
3-21-69 COMPLETION REPORTED