

12 Delaware Sand Perfs 4766-74' CAOF 1957 MCFGPD. Pot. Based
on 4-point test. SIWHP 1701#, GOR Dry, Gravity (gas) .800.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

PROP DEPTH 4850' TYPE RE

F.R. 9-5-68
PD 4850' - Del. Sd.
7-12-68 AMEND TO ADD REFERENCE NUMBER
9-9-68 TD 4850', prep log.
9-16-68 TD 4850', PBD 4822', tstg.
Perf 4766-74' W/2 SPF
Acid (4766-74') 500 gals.
Swbd & Flwd 34 BL&AW + 38 BFW + gas @ 1500 MCFGF
on 32 hr test thru 19/64" chk., TP 575#.
9-23-68 TD 4850', PBD 4822', WO Pot.
CAOF 1957 MCFGPD
9-30-68 TD 4850', PBD 4822', WO Pot.

10-14-68

TD 4850', PED 4822', COMPLETE

FOUR-POINT TESTS:

MCFGPD	Choke	Time	TP
286	1/2"	1 hr	1580#
565	3/4"	1 hr	1432#
709	7/8"	1 hr	1330#
953	1"	1 hr	1221#

LOG: Rust 830', Lamar 4714', Delaware Sand 4743'.