

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

N.M. Oil Co.
P. 1980
Hobbs, NM 88241

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT-" for such proposals

5. Lease Designation and Serial No.
NM LC064118

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Eva E. Blinebry #17

9. API Well No.

30-025-22814

10. Field and Pool, or Exploratory Area

Langlie Mattix 7 Rvrs Queen GB

11. County or Parish, State

LEA, NM

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☐ Gas Well ☒ Other WIW

2. Name of Operator

PLAINS PETROLEUM OPERATING COMPANY

3. Address and Telephone No.

415 W. WALL, SUITE 1000 MIDLAND, TX 79701 915/683-4434

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1100' FSL & 100' FEL, Sec. 35 (P), T23S, R37E

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

BLM Patricia Hutchings witnessed

12-9-97 Set 4-1/2" cement retainer @ 3350'.

Squeeze w/75 sx "C" cement @ 1-1/2 BPM @ 700 psi. Unstung & cap 2/20' of cement. TOC @ 3330'.
Pressure test csg to 500 psi & held. Circ hole w/10# mud.

Spot 20 sx "C" cement from 1600' to 1311'.

Spot 20 sx "C" cement from 410' to 121'.

Spot 20 sx "C" cement from 60' to surface.

Cut off wellhead & install dry hole marker.

Approved as to plugging of the well bore.
Liability under lease retained until
surface restoration is completed.

14. I hereby certify that the foregoing is true and correct

Signed

Donnie Husband

Title Admin. Assist.

Date 12/22/97

(This space for Federal or State office use)

(ORIG. SGD.) LES BABYAK

Title

PETROLEUM ENGINEER

Date

JAN 02 1998

Approved by

Conditions of approval, if any: