

COUNTY LEA FIELD Scarborough STATE NM 30-025-22858
 OPR ADOBE OIL CO. MAP
2 Humble-State
Sec 36, T-26-S, R-36-E CO-ORD
660' FSL, 330' FEL of Sec.
Spd 11-25-68 CLASS EL
Cmp 12-29-68

	FORMATION	DATUM	FORMATION	DATUM
CSG & SX - TUBING				
8 5/8" at 542' w/250 sx				
5 1/2" at 3280' w/250 sx				
LOGS EL GR RA IND HC A				

TD 3280'; PED 3247'

IP (Yates-Seven Rivers) Perf 3050-3232' P 55 BOPD + 130 BW. Pot based on 24 hr test. GOR 1684; Grav 29.3.

Distribution limited and publication prohibited by subscribers' agreement.
 Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Tom Brown PROP DEPTH 3300' TYPE
 DATE

F.R. 11-21-68
 PD 3300' (Seven Rivers)
 Contractor - Tom Brown
 11-26-68 TD 542'; Prep Run Casing
 12-2-68 TD 3050'; Prep Core
 12-9-68 TD 3280'; WOC
 Cored 3050-3100', rec 50' w/show in top 10"
 Cored 3100-50', rec 50', no description
 Cored 3150-3200', rec 50', no description
 Cored 3200-50', rec 50', no description
 12-17-68 TD 3280'; Prep Perf
 12-23-68 TD 3280'; PED 3247'; Swbg
 Perf 3228-32' w/1 SPF
 Acid (3228-32') 1000 gals
 Swbd 130 BF (5% oil) in 16 hrs (3228-32')
 Acid (3228-32') 5000 gals

12-23-68 Continued
Swbd 200 BF (10-15% oil) in 20 hrs
(3228-32')
Perf @ 3050', 3052', 3054', 3056', 3084',
3088', 3129', 3142', 3167', 3179', 3181'
w/1 SPI
Acid (3050-3181') 1500 gals
Swbd 10 BF in 4 hrs & swbd dry (3050-3181')
Frac (3050-3232') 31,290 gals wtr + sd
Swbd approx. 370 BF (10-15% oil) in 16 hrs
1-6-69 TD 3280'; PBD 3247'; COMPLETE
LOG TOPS: Anhydrite 1413', Base Salt 2845',
Yates 3049', Seven Rivers 3224'
1-9-69 COMPLETION REPORTED