Form 9-331
(May 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE* (Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.: LC-030168-B

6. IF INDIAN, ALLOTTEE OR TRIBE NAME:

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

JUL 6 2 16 PM '69

1. OIL WELL [X] GAS WELL [ ] OTHER

7. UNIT AGREEMENT NAME: NMFU

2. NAME OF OPERATOR: Continental Oil Company

8. FARM OR LEASE NAME: Eaves "B" 1

3. ADDRESS OF OPERATOR: Box 460, Hobbs, New Mexico 88240

9. WELL NO.: 14

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface: 1980' FNL & 660' FWL of Sec. 31, T-26S, R-37E in Lea County, New Mexico

10. FIELD AND POOL, OR WILDCAT: Scarborough Yates Seven Rivers

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA: Sec. 31, T-26S, R-37E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.): 2930 DF (est.)

12. COUNTY OR PARISH: Lea

13. STATE: N. Mex.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:				SUBSEQUENT REPORT OF:			
TEST WATER SHUT-OFF	[ ]	PULL OR ALTER CASING	[ ]	WATER SHUT-OFF	[ ]	REPAIRING WELL	[ ]
FRACTURE TREAT	[ ]	MULTIPLE COMPLETE	[ ]	FRACTURE TREATMENT	[ ]	ALTERING CASING	[ ]
SHOOT OR ACIDIZE	[ ]	ABANDON*	[ ]	SHOOTING OR ACIDIZING	[ ]	ABANDONMENT*	[ ]
REPAIR WELL	[ ]	CHANGE PLANS	[ ]	(Other) Spud Date			[X]
(Other)				(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)			

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 6-28-69 and drilled 12¼" hole, set 8⅝", 24#, J-55 casing at 500'. Cemented w/175 sacks of class "H" cement. Circulated cement to surface. WOC 24 hours. Pressured casing to 1000# for 30 minutes. Tested O.K.

18. I hereby certify that the foregoing is true and correct

SIGNED Robert Daulton TITLE Administrative Section Chief DATE 7-1-69

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____

CONDITIONS OF APPROVAL, IF ANY:

APPROVED

JUL 3 1969

J L GORDON
ACTING DISTRICT ENGINEER

USGS-5, Pan Am Hobbs 2, Atl. Rich Roa 2, Shell Mid 2, File

*See Instructions on Reverse Side