

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐

2. NAME OF OPERATOR
Amoco Production Company

3. ADDRESS OF OPERATOR
P. O. Box 68, Hobbs, NM 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 660' FNL X 1980' FEL
AT TOP PROD. INTERVAL: (Unit B, NW/4, NE/4)
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

SUBSEQUENT REPORT OF:

☒
☐
☐
☐
☐
☐
☐
☐

(other) Surface casing

5. LEASE
NM 14336

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME RECEIVED

8. FARM OR LEASE NAME SEP 9 1981
Federal CH

9. WELL NO. O. C. D.
1


10. FIELD OR WILDCAT NAME ARTESIA, OFFICE
Wildcat Delaware

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
22-26-34

12. COUNTY OR PARISH Lea 13. STATE NM

14. API NO.
30 025 27376

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3240.4' GL



(NOTE: Report results of multiple completion or zone change on Form 9-330.)

OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

On 8-20-81 Cactus Brothers (Rig #54) spudded a 12-1/4" hole at 9:00 p.m. Drilled to 960' and ran 8-5/8", 24#, K-55 surface casing. Set at 823'. Cemented with 475 sacks of Class C with 1% CaCl. Plugged down at 1:00 a.m. 8-23-81. Cement did not circulate. Tagged top of cement at 93'. Pumped 100 sacks more of Class C with 1% CaCl and cement circulated to top. Pressure tested casing to 1200 psi. Tested OK. WOC 18 hrs. Reduced hole to 7-7/8" and resumed drilling.

0+6-USGS, H 1-Hou 1-Susp 1-LBG 1-W. Stafford, Hou

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Accepted for Record TITLE Ast. Adm. Analyst DATE 9-1-81

ROGER A. CHAPMAN

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL: SEP 8 1981

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO