

COUNTY	LEA	FIELD	Salado Draw	STATE	NM	30-025-23992
OPR	MAC DONALD OIL CORP.			MAP		
1 Ammons & Madera et al						
Sec 15, T-26-S, R-33-E						
1980' FSL, 990' FWL of Sec						
Spd 1-12-72						
Cmp 2-17-72						
		FORMATION	DATUM	CLASS		EL
CSG & SX - TUBING						
8 5/8" at 379' w/250 sx						
4 1/2" at 5142' w/200 sx.						
LOGS EL GR RA IND HC A						
TD 5150'; PBD 5142'						
IP (Delaware Sand) Perfs 5002-23' P 121 BOPD. Pot based on						
24 hr test. GOR NR; Grav 40.						

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Cactus PROP DEPTH 5150' TYPE RT
DATE

F.R. 12-21-71; Opr's Elev. 3310' DF
PD 5150' RT (Delaware)
Contractor - Cactus
3-2-72 AMEND OPERATOR & FIELD NAME, Formerly reported as
Brasfield, Harold A. & Jack W. Trantham; Undesignated
Field.
1-18-72 Drlg. 5033'
Cored 4970-5020', rec 50' lm, sd & shly sd
Core Top: Delaware Sand 4982'
1-24-72 TD 5150'; WO Completion
1-31-72 TD 5150'; PBD 5142'; Istg
Perf 5002', 5006-08', 5010-12', 5018-23' w/2 SPF
Acid (5002-23') 1000 gals
Frac (5002-23') 8000 gals oil + 8000# sd

2-7-72 TD 5150'; PBD 5142'; SI
 Flwd 38 BO + 25 BW in 9 hrs
2-14-72 TD 5150'; PBD 5142'; WO Potential
2-21-72 TD 5150'; PBD 5142'; TO Pmp
 Ppd 66 BO + 35 BW in 24 hrs
2-28-72 TD 5150'; PBD 5142'; COMPLETE
 LOG TOPS: Anhydrite 905', Lamar 4955',
 Delaware Sand 4983', Ford Shale 5040',
 Olds 5071'
3-2-72 COMPLETION REPORTED