

O. C. COPIES RECEIVED		
DISTRIBUTION		
NTA FE		
LE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS <small>(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)</small>		5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
		5. State Oil & Gas Lease No. SWD - 138
1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Salt Water Disposal Well		7. Unit Agreement Name
2. Name of Operator Truckers Water Company		8. Farm or Lease Name Gulf State
3. Address of Operator P. O. Box 1196, Eunice, New Mexico		9. Well No. # 1
4. Location of Well UNIT LETTER M 660 FEET FROM THE South LINE AND 660 FEET FROM THE West LINE, SECTION 2 TOWNSHIP 23S RANGE 37E NMPM.		10. Field and Pool, or Wildcat Eunice
15. Elevation (Show whether DF, RT, GR, etc.)		12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/> TEMPORARILY ABANDON <input type="checkbox"/> PULL OR ALTER CASING <input type="checkbox"/> OTHER <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/> CHANGE PLANS <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/> COMMENCE DRILLING OPNS. <input type="checkbox"/> CASING TEST AND CEMENT JOBS <input type="checkbox"/> OTHER <input checked="" type="checkbox"/> Convert to Salt Water Disposal	ALTERING CASING <input type="checkbox"/> PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Squeezed 5½ perfs 2862-2905 w/300 sx Class C cement & 50 sx Calseal
 Squeezed 5½ perfs 3564-3681 w/400 sx Class C cement
 Re-squeezed 5½ perfs 3564-3681 w/100 sx Class C cement w/50 sx 2% Calcium Chloride
 Drilled out and set tension packer at 3950
 Injecting into perfs 4072-4144 O.H. 4484-4500

MAR 27 1974
 OIL CONSERVATION COMMISSION

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *R.D. Burke* TITLE Vice-President DATE 3-25-74
 APPROVED BY _____ TITLE _____ DATE _____
 CONDITIONS OF APPROVAL, IF ANY: Dist. 2, 3